Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!

Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832
Email & Skype: info@chipsmall.com Web: www.chipsmall.com
Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

TAMURA

REV. Status

REVISION – 05/06/02 RJ

REVISION A ADDED RoHS 06/01/06 MP

AC–DC UL/cUL ADAPTOR DC 6V 1.25A

A. Electrical specifications
1. Input voltage: AC 120V ±10% 60Hz ±0.5Hz
2. Output voltage and current: DC 6V at 1.25A

Vin	100% Load	No Load
108	4.5VDC MIN	–
120	5.5–6.5VDC	10.0VDC MAX
132	–	11.0VDC MAX

NOTE: Specification applies after 10 minutes warm–up with full load and at any operating temperature.

3. Operating temperature: –10°C to +40°C
4. Storage temperature: –20°C to +85°C
5. Operating and Storage Humidity: 0 to 95% without condensation
6. Withstand voltage: AC 1000Vrms 1 minute @ input to output

B. Typical performance data test Condition: Ta= +25°C measured after 10 minute warm–up with input at 120V 60Hz

C. Safety agencies
UL and cUL File No. E218172

D. Nameplate: Information is as follows:
Metallic letters on a black background

AC ADAPTOR
www.TamuraGroup.com
CLASS 2 POWER SUPPLY
830AS06125
INPUT AC120V 60Hz 14W
OUTPUT DC 6V 1250mA
c UL us LISTED
E218172 98VK
B MADE IN CHINA

TYPICAL PERFORMANCE CHART



E. Mechanical Specifications
All dimensions shown are nominal unless otherwise specified



PREPARED BY: K. BRENNAN				
ENGINEER: M. PITCHAI	DWG CONTROL NO. P–A7–13012 ACAD\PS\A7130121.DWG	REV A	UL/cUL DC 6V 1.25A POWER SUPPLY	830AS06125 MODEL SPECIFICATION
QUALITY CONTROL: T. CLEM	CONTENTS OF THIS DRAWING ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE		TAMURA CORPORATION OF AMERICA 43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590–6624 (951) 699–1270 FAX 9516769482	DIM: mm(In) SCL: NONE SH: 1 OF 1
APPROVED: Y. SEKIGUCHI				

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.