



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**SIM S7/400 FB4\*10 5.0M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



The front-panel adapter can be quickly and securely connected to SIEMENS S7 300/400 I/O modules. They offer inexpensive coupling of active and passive interface modules.

- Pre-assembled control cable, 4 x 10 or 1 x 40 poles
- Separate feeding of supply voltage via screw connection terminals
- Isolation of potentials via plug-in cross-connectors.

**General ordering data**

Type	SIM S7/400 FB4*10 5.0M
Order No.	<a href="#">8335910500</a>
Version	Siemens S7-400, 48 P
GTIN (EAN)	4008190915704
Qty.	1 pc(s).

**SIM S7/400 FB4\*10 5.0M**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

Length	5,000 mm	Net weight	1,362 g
--------	----------	------------	---------

**Temperatures**

Operating temperature	Storage temperature	-40...+70 °C
-----------------------	---------------------	--------------

**General properties**

Length	5,000 mm	Cable	Cable LiYY
Material	PVC	Rated cross-section	0.14 mm <sup>2</sup>
Resistance	55 mΩ/m		

**Connection data**

Connection (field side)	Plug-in connectors according to IEC 603-1 / DIN 41651 40p	Connection to PLC	Siemens S7-400
Connection to the card	6ES7 421-1BL00-0AA0, 6ES7 422-1BL00-0AA0	Supply plug-in connectors	LM 3.5mm
Supply voltage	60 V AC / 75 V DC		

**Ratings data**

Operating voltage	60 V AC / 75 V DC	Max. current per channel	1 A
-------------------	-------------------	--------------------------	-----

**Supply connection**

Type of connection	Screw connection	Clamping range, min.	0.08 mm <sup>2</sup>
Clamping range, max.	2.08 mm <sup>2</sup>	Solid, min. H05(07) V-U	0.5 mm <sup>2</sup>
Solid, max. H05(07) V-U	1.5 mm <sup>2</sup>	Flexible, min. H05(07) V-K	0.5 mm <sup>2</sup>
Flexible, max. H05(07) V-K	1.5 mm <sup>2</sup>	Wire cross-section, min. AWG	AWG 28
Wire cross-section, max. AWG	AWG 14		

**Classifications**

ETIM 3.0	EC000237	UNSPSC	26-12-16-03
eClass 5.1	27-24-22-14	eClass 6.2	27-24-92-05
eClass 7.1	27-24-92-05		

**Approvals**

Approvals



ROHS Conform

**Downloads**

 Declaration of Conformity [K370\\_11\\_10.pdf](#)