



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# Protocol-Independent Wavelength Division Multiplexing for High Volume Optical Networking Applications

IE-iMcV-WDM/2 Series



## PRODUCT FEATURES

- WDM/2 and iMcV-WDM/2 double the capacity of installed fiber by transmitting two wavelengths on one strand of fiber
- WDM/2 and iMcV-WDM/2 are speed and protocol-independent, and support 1310 nm and 1550 nm single-mode fiber
- WDM/2 chassis performs multiplexing with NO outside power requirement
- Modular, hot-swappable architecture reduces operational costs associated with product installation, upgrades and maintenance

Wavelength Division Multiplexing (WDM) is a technology that enables the transmitting of multiple, optical signals on different wavelengths over one strand of fiber. Suited for installations where fiber is limited in terms of availability, service providers and enterprise network managers can easily double their fiber capacity without incurring the costs associated with installing new fiber. Campus area network managers can deploy the WDM/2 solution, for example, to combine voice and data traffic over the same duplex fiber between company facilities.

WDM/2 and iMcV-WDM/2 are two-channel, passive, protocol and speed-independent Wavelength Division Multiplexers which allow two individual wavelengths to share one fiber pair; Full-Duplex data travels on 1310 nm and 1550 nm to virtually double the capacity of installed fiber. Deploy WDM/2 products in pairs so that the host site will multiplex 1310 nm and 1550 nm onto the fiber and the remote site will then separate the signals by the wavelength. Available in standalone and modular versions, the protocol-independent WDM/2 products enable the transmitting of any protocol and any speed over 1310 nm or 1550 nm single-mode fiber.

### Support a variety of protocols; easy installation

As passive, protocol-independent Wavelength Division Multiplexers, WDM/2 and iMcV-WDM/2 comply with a wide range of communications protocols including Ethernet (10/100/ 1000 Mbps), SONET/SDH (OC-3, OC-12 OC-48), FDDI, ATM, ESCON, T1/E1, E3, DS3, FibreChannel, and 10G. Installing WDM/2 products is easy— standalone WDM/2 chassis come ready to install and iMcV-WDM/2 modules slide into any iMediaChassis or MediaChassis/2. There is no configuration required for either version.

## ORDERING INFORMATION

MODEL NUMBER	FIBER	FIBER PORTS
<b>iMcV-WDM/2</b>		
849-14100	SC	4
<b>WDM/2 Stand Alone Chassis</b>		
849-10100	SC	4



*iView: Windows 2000/XP/Vista/Win7*

# Protocol-Independent Wavelength Division Multiplexing for High Volume Optical Networking Applications

IE-iMcV-WDM/2 Series



## SPECIFICATIONS

### TECHNICAL

Doubles the capacity of installed fiber by transmitting two wavelengths on one strand of fiber

Speed-independent

Protocol-independent; complies with a wide range of communications protocols including Ethernet (10/100/1000 Mbps), SONET/SDH (OC-3, OC-12 OC-48), FDDI, ATM, ESCON, T1/E1, E3, DS3 and FibreChannel

Supports GUI-Based iView<sup>2</sup>

Connectors: SC

Supports Half- and Full-Duplex operation

### iMcV-WDM/2

Requires two slots in a chassis; modules are double-wide

Installs in any iMediaChassis or MediaChassis/2

### WDM/2 STANDALONE CHASSIS

iMcV-WDM/2 module ships from factory in a standalone chassis

### MECHANICAL

Shipping Weight iMcV-WDM/2 0.9 lbs. (0.34 kg)

Shipping Weight WDM/2 Chassis 1.1 lbs. (0.50 kg)

### ENVIRONMENTAL

Operating Temperature +32° to +122° F (0° to +50° C)

Storage Temperature: -13° to +158°F (-25° to +70°C)

Operating Humidity 5% to 95% (non-condensing)

### REGULATORY APPROVALS

FCC Class A

UL/cUL, CSA, CE

## MECHANICAL DIAGRAM

(dimensions in inches)

