mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





| Part Number: 8504 | | | | | | |
|---|--|--|--|--|--|--|
| Hook-Up/ Lead Wire (Type B) MIL-W-16878/1-PVC, (1) 24 AWG (7x32) TC, PVC | | | | | | |
| tar and the second sec | | | | | | |

Product Description

One 24 AWG stranded (7x32) tinned copper conductor, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

| Filys | | | 11 all) |
|--------------|----------------------|--------------------|--------------------|
| Condu | ictor | | |
| AWG | Stranding | Material | No. of Conductors |
| 24 | 7x32 | TC - Tinned Copper | 1 |
| Cond | uctor Count: | 1 | |
| Cond | uctor Size: | 24 AW0 | 3 |
| Insula | tion | | |
| | Material | Nominal Diar | neter Nominal Wall |
| PVC | - Polyvinyl Ch | loride 0.044 in | 0.01 in |
| Outer | Jacket Mate | rial | |
| Mate | erial | | |
| No Ja | acket | | |
| | | | |
| Flec | trical Cha | racteristics | |
| Shiel | ding: | Unshiel | ded |
| Voltag | e | | |
| Volta | ge Rating [V | 1 | |
| 600 \ | / | | |
| Tom | perature I | Zango | |
| | | | |
| Non- | JL Temp Rati | ng: 105°C | |
| Mec | nanical Cl | haracteristics | |
| Bulk | Cable Weight | : 2 lbs/10 | 00ft |
| Stan | dards | | |
| | | | |
| | WM Style: | N/A | |
| Milita | ry Specificatio | on: MIL-W- | 16878/1 |
| Appl | icable En | vironmental an | d Other Progra |
| | irective 2000/ | 53/EC Yes | |
| (ELV | | | |
| EU D (BFR | irective 2003/): | 96/EC Yes | |

| EU Directive 2003/96/EC (BFR): | Yes | |
|---------------------------------------|-------------------------------|--|
| EU Directive 2011/65/EU (ROHS II): | Yes | |
| EU Directive 2012/19/EU (WEEE): | Yes | |
| EU Directive 2015/863/EU: | Yes | |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) | |

| EU CE Mark: | Yes |
|---------------------------------------|------------|
| EU RoHS Compliance Date (yyyy-mm-dd): | 2006-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

N/A

UL voltage rating:

Plenum/Non-Plenum

| Plenum (Y/N): No | | | |
|------------------|---------------|--|--|
| | Plenum (Y/N): | | |

Part Number

Variants

| Item # | Color | F | ootnote | |
|-------------------------------|-------------|---|---------|--|
| 8504 010100 | Black | | | |
| 8504 0101000 | Black | Ρ | | |
| 8504 006100 | Blue, Light | | | |
| 8504 0061000 | Blue, Light | Ρ | | |
| 8504 001100 | Brown | | | |
| 8504 0011000 | Brown | Ρ | | |
| 8504 008100 | Gray | | | |
| 8504 0081000 | Gray | Ρ | | |
| 8504 005100 | Green, Dark | | | |
| 8504 0051000 | Green, Dark | Ρ | | |
| 8504 003100 | Orange | | | |
| 8504 0031000 | Orange | Ρ | | |
| 8504 002100 | Red | | | |
| 8504 0021000 | Red | Ρ | | |
| 8504 0071000 | Violet | Ρ | | |
| 8504 009100 | White | | | |
| 8504 0091000 | White | Ρ | | |
| 8504 004100 | Yellow | | | |
| 8504 0041000 | Yellow | Ρ | | |
| Footnote: P - STRIF PUT-UP | | | | |

P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.