# imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





| Part Number: 8520  |
|--|
| Hook-Up/ Lead Wire (Type MW) MIL-W-76C-PVC, (1) 14 AWG (41x30) TC, PVC |
| ta Request Sample  |

#### **Product Description**

One 14 AWG stranded (41x30) tinned copper conductor, PVC insulation.

#### **Technical Specifications**

### **Physical Characteristics (Overall)**

| ,            |   |             |               | .,               |
|--------------|---|-------------|---------------|------------------|
| Cond         | uctor                                       |             |               |                  |
| AWO          | Stranding                                   | Mate        | rial No       | o. of Conductors |
| 14           | 41x30                                       | TC - Tinne  | d Copper 1    |                  |
| Con          | luctor Count:                               |             | 1             |                  |
| Con          | luctor Size:                                |             | 14 AWG        |                  |
| Insula       | tion  |             |               |                  |
|              | Material                                    | Non         | ninal Diamete | r Nominal Wall   |
| PVC          | - Polyvinyl Ch                              | loride 0.11 | 1 in          | 0.018 in         |
| Outer        | Jacket Mater                                | rial        |               |                  |
|              | erial                                       |             |               |                  |
|              | acket                                       |             |               |                  |
|              |   |             |               |                  |
| Elec         | trical Cha                                  | racterist   | ics           |                  |
| Shie         | ding:                                       |             | Unshielded    |                  |
| Volta        | ge  |             |               |                  |
| Volt         | ige Rating [V                               |             |               |                  |
| 1000         | V   |             |               |                  |
| Tom          | noroturo I                                  | Dongo       |               |                  |
|              | perature I                                  |             | _             |                  |
| Non-         | UL Temp Rati                                | ng:         | 80°C          |                  |
| Star         | dards                                       |             |               |                  |
| UL A         | WM Style:                                   |             | N/A           |                  |
|              | ry Specificatio                             | on:         | MIL-W-76C     |                  |
|              |   |             |               |                  |
| Арр          | Applicable Environmental and Other Programs |             |               |                  |
| EU E<br>(ELV | irective 2000/<br>):                        | 53/EC       | Yes           |                  |
|              | irective 2003/                              | 96/EC       | Yes           |                  |

| (BFR):                                | Yes                           |
|---------------------------------------|-------------------------------|
| EU Directive 2011/65/EU<br>(ROHS II): | Yes                           |
| EU Directive 2012/19/EU<br>(WEEE):    | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-10-01                    |

| CA Prop 65 (CJ for Wire & Cable): | Yes             |
|-----------------------------------|-----------------|
| MII Order #39 (China RoHS):       | Yes             |
| Flammability, LS0H, To            | oxicity Testing |

| UL voltage rating: | N/A |  |
|--------------------|-----|--|
| Plenum/Non-Plenum  |     |  |
| Plenum (Y/N):      | No  |  |

#### **Part Number**

Variants

| Item #       | Color              | Footnote     |
|--------------|--------------------|--------------|
| 8520 010100  | Black              |              |
| 8520 0101000 | Black              | Ρ            |
| 8520 013100  | Blue, Dark         |              |
| 8520 006100  | Blue, Light        |              |
| 8520 0061000 | Blue, Light        | Ρ            |
| 8520 001100  | Brown              |              |
| 8520 0011000 | Brown              | Ρ            |
| 8520 005100  | Green, Dark        |              |
| 8520 0051000 | Green, Dark        | Р            |
| 8520 003100  | Orange             |              |
| 8520 0031000 | Orange             | Р            |
| 8520 002100  | Red                |              |
| 8520 0021000 | Red                | Р            |
| 8520 009100  | White              |              |
| 8520 0091000 | White              | Р            |
| 8520 0181000 | White, Blue Stripe | A            |
| Footnote:    |                    | P - STRIPE C |
| Footnote:    | A                  | - STOCKEE    |

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.