

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Field bus components FBCon PA CG/M12 4way

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083

Fax: +49 5231 14-29208 www.weidmueller.com





The FBCon Fieldbus distributor is available in the industry and EEx (ia) version. They are used for coupling from 1 to 8 field devices or sensors.

They are connected via spur lines. The connection to the spur line can be made with an M12 plug or directly via an EMC cable gland. Communication and device power feed are transferred by a common 2-wire line.

The distributors offer the following features respective of the version:

- Tension-clamp connection system
- Overvoltage protection for the main line
- Current limiter for each branch line
- EMC cable gland
- M12 plug-in connectors
- External earthing contact
- Interruption-free bus operation
- Industrial version
- Bus termination integrated (not EX)
- ATEX explosion-proof version
- Pressure-equalising element
- Protection degrees IP65, IP66, IP67
- · Stainless steel versions
- PROFIBUS-PA compatible

General ordering data

FBCon PA CG/M12 4way
<u>8564080000</u>
Standard distributor, 4-way distributor, IP 66
4032248236718
1 pc(s).



Field bus components FBCon PA CG/M12 4way

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Length	125 mm	Width	80 mm
Height	37 mm	Net weight	665 g

Temperatures

Operating temperature	-40 °C+80 °C	Ambient temperature	-40 °C+80 °C
Storage temperature	-40 °C+80 °C		

Technical data

Bus system	Profibus-PA	Cable gland	branch line M12
Colour	Grey	Connection type PE	M12 spur line
Contact carrier material	Brass	Contact material	CuZnAu
Housing main material	AI - Si 12	Number of contact sockets	4
Protection degree	IP 66	Type of mounting	surface-mounted
Version	Aluminium enclosure		

Classifications

ETIM 3.0	EC000214	UNSPSC	26-12-16-03
eClass 5.1	27-25-02-01	eClass 6.2	27-24-26-08
eClass 7.1	27-24-26-08		

Product information

Descriptive text ordering data	CG = brass cable gland
	PCG = plastic cable gland
Descriptive text technical data	FBcon products cannot be used in strongly saline environment.

Approvals

Approvals



ROHS Conform	
--------------	--

Downloads

Declaration of Conformity <u>K328_01_10.pdf</u>