



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832


Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PLUGSERIES POS 24VDC/24VDC 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com



The modular kit-type system represents a new generation of plug-in optos.

At the heart is an innovative PXS or PXZ relay base. The PLUGSERIES is particularly service-friendly and the ideal link between SSR and the application.

Conventional SSR and LED indicators are simply plugged in, retaining and disassembly clips provide a secure fixing.

Pre-assembled SSR couplers round off the product range.

Plug-in ZQV 2.5 cross-connectors enable multiplexers to be set up quickly thanks to simple side-by-side mounting.

General ordering data

Order No.	8610840000
Part designation	POS 24VDC/24VDC 2A
Version	PLUGSERIES, Solid-state relay, 0...30 V DC, 2.5 A
GTIN (EAN)	4032248271467
Qty.	10 pc(s).

PLUGSERIES POS 24VDC/24VDC 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Technical data

Dimensions

Length	92 mm	Width	15.3 mm
Height	95 mm	Weight	11 g

Temperature

Storage temperature	-40 °C...+50 °C
---------------------	-----------------

Approvals

Approvals institutes	GOSTME25; CE; CURUS
----------------------	---------------------

Control side

Power rating	250 mW	Rated auxiliary voltage	No
Rated control voltage	15 V DC...30 V DC		

General data

Standards	EN 50178	Humidity	40°C / 93% rel. humidity, no condensation
Solid-state type	POWER MOS-FET		

Insulation coordination (EN 50 178)

Clearance and creepage distances for control/load side	> 8 mm	Overvoltage category	III
Pollution severity	2	Rated voltage	300 V

Load side

Protective circuit, load side	Integrated free-wheel diode	Rated auxiliary voltage	No
Rated switching current	2.5 A	Rated switching voltage	0...30 V DC
Short-circuit-proof	No	Status indicator load side	Green LED
Switch-off delay	18 ms	Switch-on delay	2 ms
Voltage drop at max. load	≤ 0.4 V		

Classifications

eClass 6.0	27-27-09-90
------------	-------------

PLUGSERIES POS 24VDC/24VDC 2A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings

Electric symbol

