

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









LEVER-NUTS™

 222 Series Compact Lever-Operated Connectors with CAGE CLAMP®, for Solid and Stranded Wire



222 Series

2, 3 or 5 Conductor Compact Connector

Cross section: 28 - 12 AWG

(stranded and solid)

Electrical specs: 600 V (1000 V signs and fixtures)

20 A maximum

Strip length: \bigcirc 9 - 10 mm / 0.37 in Maximum operating temperature: 105° C

For all connections requiring...

- Stranded / solid wires
- Wide range of wire sizes
- Combination of different wire sizes and types in one connector
- Small space consumption
- · Built-in test point
- Protection against electrical shock, touch safe
- Low installed cost and safe operation
- Maintenance-free connection
- A reusable connector








	Item No.	Packunit pcs	Item No.	Packunit	Item No.	Packunit pcs
	222-412	<u> </u>	222-413		222-415	
	222-412/K194-4045	100 pc box (1=100)	222-413/K194-4045	50 pc box (1=50)	222-415/K194-4045	40 pc box (1=40)
	222-412/PW05-0005	5 pc blister pack	222-413/PW05-0005	5 pc blister pack	222-415/PW05-0005	5 pc blister pack
			222-413/VE00-2500	2,500 pc bulk bag		
Technical Data				, , ,		
Approvals	c (UL) us		c(U) _{US}		c(VI) _{US}	
Number of connection points	2		3		5	
per connector						
Potentials per connector	1		1		1	
Connection type	CAGE C	LAMP®	CAGE CL	AMP®	CAGE CLA	MP®
Connection type	Spring pressure connection technology		Spring pressure connection technology		Spring pressure connection technology	
Height	14.5 mm/0.571 in		14.5 mm/0.571 in		14.5 mm/0.571 in	
Width	12.4 mm/0.488 in		17 mm/0.669 in		26.6 mm/1.047 in	
Depth	20.5 mm/0.807 in		20.5 mm/0.807 in		20.5 mm/0.807 in	
Color	Gray (w/ord	inge levers)	Gray (w/orange levers)		Gray (w/orange levers)	
Accessories	Item No.	Packunit	5.5, (<i>m</i> 6.4))	J. 2, (ording	, 0. 0,
Wire cutting and stripping tool (22-10 AWG)	206-130	1				

Easy as 1, 2, 3...

Operating tool for Series 222 210-101







2) Push up lever

3) Insert conductor and push down lever

Operating Tool

1) Strip wire

222 Series Mounting Carrier








Item	Packunit	Item	Packunit	ltem	Packunit		
No.	pcs	No.	pcs	No.	pcs		
Mounting carrier, oran	nge,	Strain relief plate, orange,		Universal right angle	Universal right angled adapter, gray,		
for 2-, 3- or 5-pole compact connectors		for snap-on fixing to 222-500		in combination with me	in combination with mounting carriers for		
		mounting carrier		DIN 35 rail mounting			
222-500	50 (5×10)	222-505	50 (5x10)	222	- 510 50 (5×10)		
Self-adhesive marker str	rips,						
plain 210-334	1 card						


Assembly



Snapping of lateral connector safety lock.



Mounting of strain relief plate to the mounting carrier.



Snapping the universal right angled carrier on the mounting carrier.

Mounting



Horizontal mounting with strain relief plate on DIN 35 rail using universal right angled adapter.



Strain relief by cable tie on the carrier, transverse to the connectors wiring direction. Molded marking of clamping units.



Horizontal mounting with strain relief plate on level surfaces. Testing connectors via test slots in the carrier.

WAGO Service Worldwide

Germany

WAGO Kontakttechnik Minden

Tel. ++0571/887-443 Fax ++0571/887-541

Austria

WAGO Kontakttechnik GmbH Vienna Tel. ++43/1/615 07 80

Fax ++43/1/615 07 75

Belgium

WAGO Kontakttechnik Zaventem Tel. ++32/2/7 17 90 90 Fax ++32/2/7 17 90 99

China

WAGO ELECTRONIC Co. Ltd. Tianjin Tel. ++86/22/82125854/64/74 Fax ++86/22/82125984

England WAGO, Ltd.

Rugby Tel. ++44/1788/568008

Fax ++44/1788/568050

France

WAGO CONTACT SA. Paris

Tel. ++33/148172590 Fax ++33/148632520

Italy

WAGO ELETTRONICA SRL San Lazzaro di Savena (BO) Tel. ++39/051/625-91-25 Fax ++39/051/625-91-27

Japan

WAGO Co. of JAPAN Ltd. Tokyo Tel. ++81/3/3254/8881 Fax ++81/3/3254/8885

Poland

WAGO ELWAG sp. z o. o. Wroclaw
Tel. ++48/71/33-66-626
Fax ++48/71/33-60-952

Singapore

WAGO Electronic Pte. Ltd. Singapur

Tel. ++65/2866776 Fax ++65/2842425

Switzerland

WAGO CONTACT SA Domdidier Tel. ++65/2866776 Fax ++65/2842425

Mexico

WAGO Corporation Tel. 001-800-309-5975 + 52-(55)-26-44-69-16 Fax + 52-(55)-26-44-69-15

Canada

WAGO Corporation Tel. 800 / DIN Rail (346-7245) Fax 262 / 255-3232 WAGO Corporation N120 W19129 Freistadt Road Germantown, Wisconsin 53022 Telephone: 800 / DIN Rail (346-7245) Fax: 262 / 255-3232 info.us@wago.com www.wago.us

