Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!

Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832
Email & Skype: info@chipsmall.com Web: www.chipsmall.com
Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

PLUGGABLE WITH PIN STRIPS

These unique modular terminal blocks are convenient and easy to use. They may be interlocked to achieve the required number of positions.The header pins, for both the 6 and 10 Amp models are supplied in strips of 24. Simply snap off the desired number of positions required and insert into PC board. The modular terminal block can be plugged into the header strip at anytime.

- Space saving low profile design
- Easy access horizontal wire entry
- Convenient screw head access on top of terminal block
- Headers mount easily in pre-drilled or stamped holes
- Wire guards help prevent damage to conductors
- Accepts #22-16 AWG wire
- Because of accumulating tolerances, we recommend a maximum of 24 positions per row
- Header strips and terminal blocks sold separately

SPECIFICATIONS

MATERIAL:
Contact: Brass, Tin Plate
Header Pins: Brass, Tin Plate
Housing: Blue PBT, UL Rated 94V-0
Screw: Steel, Zinc Plate & Clear Chromate (captivated)

ELECTRICAL:
Dielectric Strength: 2500V
Insulation Breakdown: 1500V AC/min.
Rated voltage: 250V

MECHANICAL:
Operating Temp:
22°F to 248°F (-30°C to 120°C)
Peak Temp: +393°F (+200°C)

HORIZONTAL ENTRY

- Use header strip to connect to PCB



8723

8722



Recommended Mtg. Hole Size: .047(1.19)

8724

Pin Header Strips
(24 pins per strip)
CAT. NO. 8724

3.5mm SPACING			
CAT. NO.	POSITIONS	A DIM.	CURRENT RATING
8722	2	.276 (7.0)	6 Amps
8723	3	.413 (10.5)	

HORIZONTAL ENTRY

- Use header strip to connect to PCB



8726

8725



Recommended Mtg. Hole Size: .059 (1.50)

8727

Pin Header Strips
(24 pins per strip)
CAT. NO. 8727

5mm SPACING			
CAT. NO.	POSITIONS	A DIM.	CURRENT RATING
8725	2	.394 (10.0)	10 Amps
8726	3	.591 (15.0)	

NOTES