



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**INSTA  
CP SNT 48W 24V 2A**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com



One-phase switched-mode power unit in installation housing in performance classes 24 and 48 W. .  
 The INSTA power units can be universally deployed because of their wide input range from 85 V AC to 265 V AC.  
 They are available with output voltages from 5 V to 48 V.

**General ordering data**

Order No.	<a href="#">8739140000</a>
Part designation	CP SNT 48W 24V 2A
Version	Power supply, switch-mode power supply unit
GTIN (EAN)	4032248411924
Qty.	1 pc(s).

**INSTA  
CP SNT 48W 24V 2A**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Technical data**

**Dimensions (1)**

Weight	0.2 kg	Length	62.5 mm
Width	70 mm	Height	90.5 mm

**temperature**

Ambient temperature (operational)	Storage temperature	-20 °C...+85 °C
-----------------------------------	---------------------	-----------------

**Input**

Conductor connection system	Screw connection	Input current	500 mA at rated load @ 230 V AC
Input current at 115 Vac	500 mA	Input current at 230 Vac	500 mA
Input frequency	50/ 60 Hz	Input fuse	Fusible link 2.5 A (T) / 250 V
Input voltage (voltage mode input)	85...264 V AC / 110...370 V DC	Rated control voltage	115 / 230 V AC (85...264 V AC, 110...370 V DC)
making current limit	Yes		

**output**

Conductor connection system	Screw connection	Control at 10...100% load	1 %
Mains failure bridge-over time	11 ms @ 115 V AC / 50 ms @ 230 V AC	Mains failure bridge-over time for 115 V AC	11 ms
Mains failure bridge-over time for 230 V AC	50 ms	Max. capacitance at output	8000 µF
Max. residual ripple	120 mV <sub>SS</sub>	Output current	2 A
Output power, max.	48 W	Output voltage	(adjustable via potentiometer)
Output voltage type	DC	Output voltage, max.	28 V
Output voltage, min.	15 V	Overload protection	105 %...150 % I <sub>const</sub> of max. output load; automatic reset
Parallel connection option	Max. 3 devices (rated voltages are to be calibrated at ±20 mV)	Surge protection	Varistor
rated output voltage	24 V DC ± 1 %		

**General data**

Ambient temperature (operational)	DIN Rail compatibility	TS 35
Degree of efficiency at max. load	Depth	80 mm
EMC standards	Installation advice	For side-by-side mounting, clearance: above/below > 8 mm
	Standards	EN 50178 (PELV) EN 60950 (SELV)
Mounting position, installation notice	Ambient temperature (operational)	-10 °C...+70 °C (derating from 55 °C)
Status indication		

**Insulation coordination**

Humidity at operating temperature	5...95 % (indoors), Tu = 40°C, no condensation	electrical isolation, I/O rail	4 kV
electrical isolation, input-earth	1.5 kV	electrical isolation, input-output	3 kV
electrical isolation, output-earth	0.5 kV		

**Connection data**

Clamping range, nom.	2.5 mm <sup>2</sup>	Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>		

Creation date September 3, 2010 10:31:17 PM CEST

Last update 28.06.2010 / We reserve the right to make technical changes.

**Datasheet****INSTA  
CP SNT 48W 24V 2A****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
[www.weidmueller.com](http://www.weidmueller.com)**Technical data****Approvals**

Approvals institutes	CE; CCSAUS; CULUS; CURUS; UL; CLASS2
----------------------	---

**Classifications**

eClass 5.1	27-04-90-02	eClass 6.0	27-04-90-04
------------	-------------	------------	-------------

**Notes**

Note, technical data	The internal varistor found in a switch-mode power supply does not replace the need for surge protection within a system.
----------------------	---

**Datasheet**

**INSTA  
CP SNT 48W 24V 2A**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Electric symbol**

---

