



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



87 610 050 SERIES TOTALIZING COUNTER

- Voltage Input Version
- 8 Digit .3" High LCD Display
- NEMA 4 Front Panel
- Screw Terminal
- Custom CMOS Technology




GENERAL FEATURES:

The 87 601 050 Series is a totalizing counter housed in a DIN-sized (24 x 48mm) enclosure. Count input and reset input can be a 5 to 50 VAC/DC and 48 to 240 VAC voltage pulse. The unit is powered by an internal lithium battery which can be disconnected via a dip-switch for storage purposes.

WIRING:

87 610 050



- 1 - 48 to 240 VAC Reset Input
- 2 - OV Reset Input
- 3 - 5 to 50 VAC/DC Reset Input
- 4 - 5 to 50 VAC/DC Count Input
- 5 - OV Count Input
- 6 - 48 to 240 VAC Count Input



SPECIFICATIONS:

Display	8 Digit LCD	
Display Height	0.3"	
Input		
Count/Reset Inputs	Voltage Pulse	5 to 50 VAC/DC 48 to 240 VAC
Input Speed	40 Hz	
Min. low level time	12 ms	
Min. high level time	12 ms	
Power Supply	Internal lithium battery (8 year life)	
Connection	Screw Terminals	
Front Panel Rating	NEMA 4 (IP66)	
Operating Temperature	+14°F to 122°F (-10 to 50°C)	
Storage Temperature	-13°F to 158°F (-25 to 70°C)	
Weight	2.1 oz. (60g)	

DIMENSIONS: (mm)



ORDERING INFORMATION:

Voltage Input Version 87 610 050

Products and specifications subject to change without notice.
Consult factory for application assistance.