



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: [info@chipsmall.com](mailto:info@chipsmall.com) Web: [www.chipsmall.com](http://www.chipsmall.com)

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**MI8DI-S SUB D15S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Specific adapter to be connected to the MICROSERIE RELAYS using a 10-pole flat-cable connector or 15-pole Sub-D connector.

**General ordering data**

Type	MI8DI-S SUB D15S
Order No.	<a href="#">8773460000</a>
Version	IEC 60603/DIN41612 plug-in connectors, Screw connection
GTIN (EAN)	4032248441990
Qty.	1 pc(s).

## MI8DI-S SUB D15S

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

## Technical data

## Dimensions and weights

Length	48 mm	Width	59 mm
Height	53 mm	Net weight	88 g

## Temperatures

Operating temperature	0...+55°C	Ambient temperature	0 °C...+55 °C
Storage temperature	-20...+85 °C		

## Connection data

Connection on control side	IEC 60603/DIN41612 plug-in connectors	Number of poles (control side)	25-pole plug
Supply voltage	24 V DC	Supply plug-in connectors	TOP 1.5GS2/180

## Ratings data

Operating voltage	30 V UC	Max. current per channel	0.5 A
Total operating current	2 A		

## Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

## Supply connection

Type of connection	Screw connection	Clamping range, min.	2.5 mm <sup>2</sup>
Clamping range, max.	0.13 mm <sup>2</sup>	Solid, min. H05(07) V-U	2.5 mm <sup>2</sup>
Solid, max. H05(07) V-U	0.5 mm <sup>2</sup>	Flexible, min. H05(07) V-K	2.5 mm <sup>2</sup>
Flexible, max. H05(07) V-K	0.5 mm <sup>2</sup>	Flexible with sleeve, max.	0.5 mm <sup>2</sup>
Flexible with sleeve, min.	2.5 mm <sup>2</sup>	Ferrule with plastic collar, max.	0.5 mm <sup>2</sup>
Wire cross-section, min. AWG	AWG 14	Wire cross-section, max. AWG	AWG 26
Tightening torque, min.	0.4 Nm	Tightening torque, max.	0.5 Nm
Stripping length	10 mm		

## Classifications

ETIM 3.0	EC001421	UNSPSC	30-21-18-01
eClass 5.1	27-24-22-02	eClass 6.2	27-24-22-02
eClass 7.1	27-24-22-02		

## Product information

Descriptive text ordering data	MI8DI-S = screw connection MI8DI-Z = tension clamp connection
--------------------------------	--

**Data sheet**

**MI8DI-S SUB D15S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Approvals**

Approvals



ROHS

Conform

**Downloads**

Declaration of Conformity

[K274\\_10\\_04.pdf](#)

**Data sheet**

**MI8DI-S SUB D15S**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

