



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## JACKPAC JP TEST

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The following products are available as functional components:

- Switch and button components in a sealed built-in EG2 enclosure
- Rectifier and fuse components in a sealed built-in EG2 enclosure
- Logic components with AND, NAND, OR and NOR operators
- Diode gates with up to 40 inputs in open design
- Components modules for the integration of electronic elements
- Serial interface converter, and AD / DA converter

### General ordering data

Order No.	<a href="#">8794120000</a>
Type	JP TEST
Version	JACKPAC, Relays, Rated control voltage: 18...24...30 V DC, Continuous current: 2 A, M12 plug/socket, A-coded
GTIN (EAN)	4032248483969
Qty.	1 pc(s).

**JACKPAC  
JP TEST**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	83 mm	Width	36 mm
Height	14.4 mm	Net weight	36 g

**Temperatures**

Operating temperature	0 °C...+55 °C	Ambient temperature	0 °C...+55 °C
Storage temperature	-25 °C...+70 °C		

**Input**

Rated control voltage	18...24...30 V DC	Rated current DC	2.2 mA (LED)
Status indicator	Green LED		

**Output**

Continuous current	2 A	Power	2.2 mA at 24 V
--------------------	-----	-------	----------------

**Rated data**

Conductor connection system	M12 plug/socket, A-coded
-----------------------------	--------------------------

**Insulation coordination (EN 50 178)**

Protection degree	IP 67
-------------------	-------

**Classifications**

ETIM 3.0	EC001134	UNSPSC	30-21-18-01
eClass 6.0	27-20-11-90	eClass 7.0	27-20-11-90

**Approvals**

Approvals

