



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Scotch® Filament Tape 880



Technical Data

June, 2014

Product Description

Scotch® Filament Tape 880 is a high performance tape reinforced with continuous, polyester yarn filaments that give the tape high tensile strength, high impact resistance and high cut resistance. The polypropylene film backing provides excellent abrasion and moisture resistance. The aggressive packaging grade adhesive is specifically formulated to provide an excellent balance of high initial adhesion and long term holding power to fiberboard, “non-oily” metals, printed and painted surfaces.

Product Construction

Backing	Adhesive	Reinforcement	Backing Color
Polypropylene film	Pressure sensitive synthetic rubber resin	Polyester yarn	Clear, Black, Blue, or Red

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	80 oz./in. width (88 N/100 mm width)	D-3330
Tensile Strength:	270 lbs./in. width (4725 N/100 mm width)	D-3759
Elongation at Break:	19%	D-3759
Total Thickness:	7.7 mil (0.196 mm)	D-3652

Features

- Good handling.
- Printable (clear only).
- Cut and impact resistant.
- High shear adhesion.
- Excellent aging.
- Tough film backing protects the filaments and adhesive to provide longer functional tape performance.
- Good handling characteristics saves time through ease of dispensing and tape application.
- When printed, the tape provides advertising, warning, and labeling capability.
- The polyester filaments resist cutting when tabbing the end lap of metal coils.
- The polyester filaments absorb the shock of rough, high impact handling to keep package secure during shipping.
- High tensile strength allows the use of less tape in many applications and lowers the cost per application.
- Translucency of the clear version allows good clarity of artwork and important messages, even when covered by the tape.
- Adhesive provides good holding under wide range of application conditions with minimum amount of tape.
- Holds instantly with minimum rubdown.
- Boxes remain securely closed through normal warehouse time cycles.

Scotch® Filament Tape

880

Available Sizes	Standard Widths: 0.35 in. (9 mm), 0.47 in. (12 mm), 0.59 in. (15 mm), 0.71 in. (18 mm), 0.94 in. (24 mm), 1.2 in. (30 mm), 1.4 in. (36 mm) and 1.9 in. (48 mm)
	Core Size (ID): 3 in. (76.2 mm)
	Lengths: 60 yds. (55 m)

Storage Conditions	Store behind present stock. Store in a clean, dry place. Temperature of 40-80°F (4-26°C) and 40-50% relative humidity are recommended. Rotate your stock.
---------------------------	---

Shelf Life	To obtain best performance, use this product within 18 months from date of manufacture.
-------------------	---

Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
------------------------------	--

Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.
--------------------	--

Warranty, Limited Remedy, and Disclaimer	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
---	---

Limitation of Liability	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.
--------------------------------	--



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

Scotch is a registered trademark of 3M.
Printed in U.S.A.
©3M 2014 (6/14)