



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**MICRO-Interface  
MI8A-I/O S SUBD15B**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Specific adapter to be connected to the MICROSERIE RELAYS using a 10-pole flat-cable connector or 15-pole Sub-D connector.

**General ordering data**

Type	MI8A-I/O S SUBD15B
Order No.	<a href="#">8800220000</a>
Version	Adapter, MICRO-Interface, IEC 60603/DIN41612 plug-in connectors, Screw connection
GTIN (EAN)	4032248497157
Qty.	10 pc(s).

**Data sheet**

**MICRO-Interface  
MI8A-I/O S SUBD15B**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	32 mm	Width	61 mm
Height	42 mm	Net weight	31.8 g

**Temperatures**

Operating temperature	0...+50°C	Storage temperature	-20...+85 °C
-----------------------	-----------	---------------------	--------------

**Connection data**

Connection on control side	IEC 60603/DIN41612 plug-in connectors	Number of poles (control side)	15-pole female
Supply voltage	max. 30 V AC/DC		

**Ratings data**

Operating voltage	30 V UC	Max. current per channel	0.5 A
Total operating current	2 A		

**Insulation coordination (EN50178)**

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

**Supply connection**

Type of connection	Screw connection
--------------------	------------------

**Classifications**

ETIM 3.0	EC001121	UNSPSC	30-21-18-01
eClass 6.2	27-24-22-08	eClass 7.1	27-24-22-08

**Approvals**

Approvals



ROHS	Conform
------	---------