



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**Industrial Ethernet
IE-C5ED8UG0020A46A46-X**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Assembled IE cables, SnapIn connectors according to IEC
61076-3-106 ver.6

General ordering data

Order No.	8829720000
Type	IE-C5ED8UG0020A46A46-X
Version	Dragline cable, RJ45 IP 67 snap-in V06 plastic, RJ45 IP 67 V 06, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PUR, 2 m
GTIN (EAN)	4032248533886
Qty.	1 pc(s).

Industrial Ethernet IE-C5ED8UG0020A46A46-X

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	2 m	Net weight	160 g
--------	-----	------------	-------

Temperatures

Operating temperature	-40 °C...+80 °C	Storage temperature	-40 °C...+80 °C
Installation temperature	-20 °C...+60 °C		

Electrical properties

Insulation resistance	500.000 Ω	Operating voltage	100 V
-----------------------	-----------	-------------------	-------

Standards

Impervious to smoke	According to IEC 61034-2	Connector standard	IEC 60603-7-51
Standard, assembly	UL-Style 20963 (80°C/30V)	Standard, insulating material	DIN EN 50290-2-25 (HD 624.5)
Standard, wire material	DIN EN 13602 Cu-ETP-A	Standard, shielding material	DIN EN 13602 Cu-ETP- A..B

Cable structure

Wire material	Stranded tin-plated copper wire	Standard designations	L19Y(ST)C11Y 4X2X0.14 VZN GN, SF/UTP
Strands	7	Cross-section	4*2*AWG 26/7 - 4*2*0.128 mm ²
Insulation cross-section	0.95 mm	Wire core insulation thickness	0.23 mm
Arrangement of wire cores	Twisted pair	Diameter of wire pair	1.9 mm
Colour sequence or wires - wire pairs	white/blue - blue, white/ orange - orange, white/ green - green, white/ brown - brown	Filler	As central element, Between the individual wire pairs
Shielding	SF/UTP	Complete shielding	Plastic foil, Aluminium foil, Shielding braid made from copper wiring
Shielding braid thickness	0.1 mm	Overlap of shielding braid	90 %
Material sheath	PUR	Sheath diameter, min.	6.3 mm
Sheath diameter, max.	6.8 mm	Sheathing material thickness	0.85 mm
Sheathing colour	green (RAL 6018)		

Electrical properties of cable

Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)	Operating voltage	100 V
Operating voltage, UL	30 V	Test voltage: wire-wire-shield, at RMS 50Hz, 1 min.	700 V
Characteristic impedance	100 ± 5 Ω at 100MHz	Loop resistance	270 Ω/km
Deviation	40 ns/100m	Resistance differential	2 %
Transfer impedance	100 mΩ/m at 10 MHz	Insulation resistance	500.000 Ω
Capacity at 800 Hz	50 nF/km	Signal propagation time	5.55 ns/m

**Industrial Ethernet
IE-C5ED8UG0020A46A46-X**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Mechanical and material properties of cable

Min. bending radius, once only	4 *diameter	Min. bending radius, repetitive	7.5 *diameter
Pulling force	≤ 100 N	Speed	180 m/min
Acceleration	5 m/s ²	Torsion resistance	30 °/m
Abrasion resistance	very good	Resistance to spread of flame	in accordance with IEC 60332-1
Resistance to oils	in accordance with IEC 60811-2-1	UV-resistant	Yes
Silicone-free	Yes	Halogen	in accordance with IEC 60754-2
Impervious to smoke	According to IEC 61034-2	Fire propagation	No

plug

Version connector left	RJ45 IP 67 snap-in V06 plastic	Version connector right	RJ45 IP 67 V 06
------------------------	--------------------------------	-------------------------	-----------------

Classifications

ETIM 2.0	EC001262	ETIM 3.0	EC001262
UNSPSC	26-12-16-06	eClass 4.1	27-06-08-05
eClass 5.1	27-06-18-02	eClass 6.2	27-06-18-01
eClass 7.1	27-06-18-01		

Approvals

Approvals	
ROHS	Conform

**Industrial Ethernet
IE-C5ED8UG0020A46A46-X**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Wiring**

RJ45	1	white, orange	1	RJ45
	2	orange	2	
	3	white, green	3	
	4	blue	4	
	5	white, blue	5	
	6	green	6	
	7	white, brown	7	
	8	brown	8	
