



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**RIDERSERIES
SCM-I QV P**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Cross-connector for bridging connections in the
RIDERSERIES RCM

General ordering data

Order No.	8870850000
Type	SCM-I QV P
Version	RIDERSERIES, Cross-connector, No. of contacts: 2, Continuous current: 12 A
GTIN (EAN)	4032248631698
Qty.	10 pc(s).

**RIDERSERIES
SCM-I QV P**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Ratings

Humidity 40 °C / 93 % rel. humidity,
no condensation

Dimensions and weights

Width 23 mm Net weight 1.2 g

Temperatures

Operating temperature -45 °C...+70 °C Storage temperature -40 °C...+85 °C

Output

Continuous current 12 A

Contact specifications

No. of contacts 2

Insulation coordination

Protection degree IP 20

Classifications

ETIM 3.0	EC000489	UNSPSC	30-21-19-17
eClass 5.1	27-37-16-03	eClass 6.0	27-37-16-03
eClass 7.0	27-37-16-03		

Approvals

Approvals

