imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



HDC housing;bulkhead housing IE-X-USB/USB



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





{Reference (Object) not found: prodxxxxxxxxxxx}}

General ordering data

Order No.	<u>8910980000</u>	
Туре	IE-X-USB/USB	
Version	USB, Type A, socket - socket	
GTIN (EAN)	4032248667550	
Qty.	5 pc(s).	

HDC housing;bulkhead housing IE-X-USB/USB

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and wei	ights		
Length	32.5 mm	Width	20.6 mm
Height	21.45 mm	Net weight	19 g
Temperatures			
Operating temperature			
Technical data			
Height	21.45 mm	Length	32.5 mm
Operating temperature		Version	USB, Type A, socket - socket
Colour	Black		
Classifications			
ETIM 3.0	EC000830	eClass 6.2	27-06-91-90
eClass 7.1	27-06-91-90		
Approvals			
ROHS	Conform		