

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China










## 2.5 x 2.0 mm SMD CMOS CXO 8W SERIES




## **Features**

- > Ultra Small SMD seam sealed clock crystal oscillator units.
- > For applications in WLAN, Bluetooth, DSC, DSL and other IT product.
- > Tri-state function available.
- > RoHS Compliant / Pb Free

## **Electrical Specifications**

| Item / Type                     | 8W                                   |
|---------------------------------|--------------------------------------|
| Output Type                     | CMOS                                 |
| Output Load                     | 15 pF                                |
| Oscillation Mode                | Fundamental                          |
| Supply Voltage                  | 3.3 V (1.8 V , 2.5 V available)      |
| Frequency Range                 | 4 ~ 54 MHz                           |
| Frequency Stability             | ± 25 ppm (-10 ~ + 70 °C), or specify |
| Operating Temperature Range     | - 40 ~ + 85 °C                       |
| Storage Temperature Range       | - 55 ~ + 125 °C                      |
| Voltage Vol (Max.) / Voh (Min.) | 0.1 VDD / 0.9 VDD                    |
| Rise (Tr) / Fall (Tf) Time      | 8 ns Max.                            |
| Supply Current                  | 15 mA Max.                           |
| Symmetry                        | 45 ~ 55 %                            |
| Start-up Time                   | 5 ms Max.                            |
| Phase Jitter (12 KHz ~ 20 MHz)  | 2 ps Max.                            |
| Aging (at 25 °C)                | ± 3 ppm / year Max.                  |

#### **Dimensions**



Units:mm