imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SPECIFICATION CONTROL DRAWING



MATERIALS

1. INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.

Recovered Dimensions: I.D.: 2.41 (0.095)

Wall Thickness: 0.33 min. (0.013 min)

2. SEALING INSERTS: Fluorocarbon-based thermoplastic, Color: natural.

APPLICATION

- 1. This part is designed to provide an environment resistant seal on stub or parallel splices, having no more than two wires, rated for at least 135°C, exiting from either end of sleeve.
- 2. To install part, make crimp in usual manner and insert into sleeve so that crimp barrel enters end of tapered insert. Heat sleeve using a Raychem approved convection heater. Apply heat first to large end of sleeve until the insert flows along the wires, then heat other insert until it flows.
- 3. Maximum weight of part: 0.47 grams.

Raychem Interconnect a division of Liectronics 300 Constitution Drive Menlo Park, CA 94025, USA					RMOFIT EVICES	TIT	TITLE : SEALING SLEEVE, STUB SPLICE				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.							DOCUMENT NO.: D-436-45				
TOLERANCES:	ANGLES: N/A		Raychem reserves the right to amend this				DCR NUMBER:		REPLACES:	REPLACES:	
0.00 N/A 0.0 N/A			0	rawing at any time. Users should evaluate			D000567		N/A		
0.0 N/A 0 N/A			the suitability of the product for their application.								
DRAWN BY:		DATE:			PROD. REV.		DOC ISSUE:	SCALE:	SIZE:	SHEET:	
M. FORONDA		02-Oct-00		K		1	None	А	1 of 1		

If this document is printed it becomes uncontrolled. Check for the latest revision.