



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





General ordering data

Order No.	9009440000
Part designation	BIT E6,3 1,0x5,5x50
Version	Screwdriver insert, Slotted, Blade width (B): 5.5 mm, Blade length (C): 50 mm, Blade thickness (A): 1.0 mm
EAN	4032248267477
Qty.	5 pc(s).

Technical data

Length	50 mm
Weight	10.2 g

Product data

Blade thickness (A)	1 mm
Blade width (B)	5.5 mm
Blade length (C)	50 mm
Blade type	Slotted
Version	E 6.3 DIN 3126

Approvals

Approvals institutes	n.a.
----------------------	------

Classifications

ETIM 2.0	EC000158
ETIM 3.0	EC000158
eClass 4.1	21-04-04-02
eClass 5.0	21-04-04-02
eClass 5.1	21-04-04-02

Similar products

Order No.	Part designation	Version
-----------	------------------	---------

9202750000	BIT E6,3 0,4x2,5x70	Screwdriver insert, Slotted, Blade width (B): 2.0 mm, Blade length (C): 70 mm, Blade thickness (A): 0.4 mm
9009410000	BIT E6,3 0,5x3,0x50	Screwdriver insert, Slotted, Blade width (B): 3.0 mm, Blade length (C): 50 mm, Blade thickness (A): 0.5 mm
9024000000	BIT E6,3 0,5x3,0x70	Screwdriver insert, Slotted, Blade width (B): 3.0 mm, Blade length (C): 70 mm, Blade thickness (A): 0.5 mm
9205600000	BIT E6.3 0.5X3.0X110	Schraubendrehereinsatz, Klinge: Schlitz, Klingenbreite (B): 3.0 mm, Klingenlänge (C): 110 mm, Klingenstärke (A): 0.5 mm
9009420000	BIT E6,3 0,6x3,5x50	Screwdriver insert, Slotted, Blade width (B): 3.0 mm, Blade length (C): 50 mm, Blade thickness (A): 0.6 mm
9024020000	BIT E6,3 0,6x3,5x70	Screwdriver insert, Slotted, Blade width (B): 3.0 mm, Blade length (C): 70 mm, Blade thickness (A): 0.6 mm
9205610000	BIT E6.3 0.6X3.5X110	Schraubendrehereinsatz, Klinge: Schlitz, Klingenbreite (B): 3.5 mm, Klingenlänge (C): 110 mm, Klingenstärke (A): 0.6 mm
9009430000	BIT E6,3 0,8x4,0x50	Screwdriver insert, Slotted, Blade width (B): 4.0 mm, Blade length (C): 50 mm, Blade thickness (A): 0.8 mm
9024030000	BIT E6,3 0,8x4,0x70	Screwdriver insert, Slotted, Blade width (B): 4.0 mm, Blade length (C): 70 mm, Blade thickness (A): 0.8 mm
9205620000	BIT E6.3 0.8X4.0X110	Schraubendrehereinsatz, Klinge: Schlitz, Klingenbreite (B): 4.0 mm, Klingenlänge (C): 110 mm, Klingenstärke (A): 0.8 mm
9205630000	BIT E6.3 0.6X4.5X110	Schraubendrehereinsatz, Klinge: Schlitz, Klingenbreite (B): 4.5 mm, Klingenlänge (C): 110 mm, Klingenstärke (A): 0.8 mm
9024040000	BIT E6,3 1,0x5,5x70	Screwdriver insert, Slotted, Blade width (B): 5.5 mm, Blade length (C): 70 mm, Blade thickness (A): 1.0 mm
9205640000	BIT E6.3 1.0X5.5X110	Schraubendrehereinsatz, Klinge: Schlitz, Klingenbreite (B): 5.5 mm, Klingenlänge (C): 110 mm, Klingenstärke (A): 1.0 mm
9202740000	BIT E6,3 1,2x6,5x70	Screwdriver insert, Slotted, Blade width (B): 6.5 mm, Blade length (C): 70 mm, Blade thickness (A): 1.2 mm
9205650000	BIT E6.3 1.2X6.5X110	Schraubendrehereinsatz, Klinge: Schlitz, Klingenbreite (B): 6.5 mm, Klingenlänge (C): 110 mm, Klingenstärke (A): 1.2 mm
9025570000	BIT E6.3 Z 0.6X3.5X39	Screwdriver insert, With peg for sockets, Blade width (B): 3.0 mm, Blade length (C): 39 mm, Blade thickness (A): 0.6 mm
9205670000	BIT E6.3Z 0.6X3.5X70	Schraubendrehereinsatz, Klinge: mit Zapfen für Steckbuchsen, Klingenbreite (B): 3.5 mm, Klingenlänge (C): 70 mm, Klingenstärke (A): 0.6 mm
9025590000	BIT E6.3 Z 0.8X4.0X39	Screwdriver insert, With peg for sockets, Blade width (B): 4.0 mm, Blade length (C): 39 mm, Blade thickness (A): 0.8 mm
9205660000	BIT E6.3Z 0.8X4.0X70	Schraubendrehereinsatz, Klinge: mit Zapfen für Steckbuchsen, Klingenbreite (B): 4.0 mm, Klingenlänge (C): 70 mm, Klingenstärke (A): 0.8 mm