



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Adapters, Between Series Straight, Plug to Plug or Plug to Jack

<p>Fig. 1</p> <p>N Plug to SMA Plug 901-292 VSWR: 1.3 max. DC-12.4 GHz</p>	<p>Fig. 2</p> <p>N Plug to SMA Jack 901-294 VSWR: 1.3 max. DC-12.4 GHz</p>	<p>Fig. 3</p> <p>N Plug to TNC Jack 78800 VSWR: 1.35 max. DC-11 GHz</p>	
<p>Fig. 4</p> <p>N Plug to UHF Jack 4400 (UG-146/U)</p>	<p>Fig. 5</p> <p>SMA Plug to SMB Plug (Female Contact) 901-9038 VSWR: 1.08 max. DC-4 GHz</p>	<p>Fig. 6</p> <p>SMA Plug to TNC Plug 901-168 VSWR: 1.3 max. DC-4 GHz</p>	
<p>Fig. 7</p> <p>SMA Plug to APC-7 131-91038</p>			

Adapters

STRAIGHT ADAPTERS - PLUG TO PLUG OR PLUG TO JACK

Adapter Ends		Dimension, inch (millimeters)		Notes		Military Number	Amphenol Number	Fig.
		a	b	Plt.	Ins.			
N Plug	SMA Plug	1.70 (43.2)	.812 (20.6) dia.	P52	D1	-	901-292	1
N Plug	SMA Jack	1.66 (42.1)	.812 (20.6)	P9	D1	-	901-294	2
N Plug	TNC Jack	1.94 (33.3)	.813 (20.6)	P1	D1	-	78800	3
N Plug	UHF Jack	1.41 (35.7)	.813 (20.6)	P1	D6/8	UG-146/U	4400	4
SMA Plug	SMB Plug	.875 (22.2)	.312 (7.9) hex.	P29	D1	-	901-9038	5
SMA Plug	TNC Plug	1.12 (28.6)	.593 (15.1) dia.	P51	D1	-	901-168	6
SMA Plug	APC-7	1.39 (35.3)	.865 (22.0)	P29	D1	-	131-91038	7