

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Crimping tool CTI 6 ZERT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



Crimping tools for insulated connectors

cable lugs, terminal pins, parallel and serial connectors, plug-in connectors

- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation
- With stop for exact positioning of the contacts.
- Tested to DIN EN 60352 part 1

General ordering data

<u>9017290000</u>		
CTI 6 ZERT		
Crimping tool, Crimping tool for contacts, 0.5 mm ² , 6 mm ² , Double crimp		
4008190239084		
1 pc(s).		



Crimping tool CTI 6 ZERT

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Length	250 mm	Weight	730 g
Net weight	825 g		
Contact description	C		
Type of contact	Insulated connector	Crimping range, min.	0.5 mm ²
Crimping range, max.	6 mm²		
Tool data - crimping			
Tool data Chinping			
Crimping profile 1, min.	0.5 mm ²	Crimping type/profile	Double crimp
Crimping profile 1, max.	1.5 mm²	Crimping profile 2, min.	1.1 mm²
Crimping profile 2, max.	2.5 mm ²	Crimping profile 3, min.	2.6 mm ²
Crimping profile 3, max.	6 mm²		
Classifications			
eClass 6.0	21-04-38-90		
Product information			
Descriptive text ordering data	Additional accessories can be found in Chapter J		