



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



**PZ 4 ZERT****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Crimping tools for wire end ferrules, with and without plastic collars**

- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation

**General ordering data**

Order No.	<a href="#">9017300000</a>
Type	PZ 4 ZERT
Version	Crimping tool for wire-end ferrules, 0.5 mm <sup>2</sup> , 4 mm <sup>2</sup> , Trapezoidal crimp
GTIN (EAN)	4008190279318
Qty.	1 pc(s).

**PZ 4 ZERT****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****Dimensions and weights**

Length	200 mm	Weight	448 g
Net weight	471 g		

**Contact description**

Type of contact	Wire-end ferrules with/ without plastic collars	Crimping range, min.	0.5 mm <sup>2</sup>
Crimping range, max.	4 mm <sup>2</sup>		

**Tool data - crimping**

Crimping type/profile	Trapezoidal crimp
-----------------------	-------------------

**Classifications**

eClass 6.0	21-04-38-90
------------	-------------

**Product information**

Descriptive text ordering data	Additional accessories can be found in Chapter J
Descriptive text accessories	Information and ordering data for wire-end ferrules - see Chapter J Accessories wire-end ferrules

**Data sheet...**

**PZ 4 ZERT**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

