# mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




## H4,0/15TS OR



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code
- other colour code

#### General ordering data

Order No.	<u>9036230000</u>
Туре	H4,0/15TS OR
Version	Wire end ferrule, 4 mm <sup>2</sup> , 8 mm, Orange
GTIN (EAN)	4032248068029
Qty.	500 pc(s).

## H4,0/15TS OR

# **Technical data**

**Dimensions and weights** 



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Length	15 mm	Net weight	0.226 g
Product data			
Conductor cross-section		Wire connection cross section AWG,	
	4 mm <sup>2</sup>	max.	AWG 12
Contact surface length (L2)	8 mm	Contact surface diameter (D1)	2.8 mm
Collar diameter (D2)	4.8 mm	Metal sleeve thickness (S1)	0.2 mm
Plastic collar thickness (S2)	0.3 mm		
ETIM 2.0	EC00005	ETIM 3.0	EC000005
UNSPSC	31-16-31-02	eClass 4.1	27-06-07-01
	27-40-02-01		
eClass 5.1		eClass 6.0	27-40-02-01
eClass 7.0	27-40-02-01		
Product information			
	Wire end ferrule with plastic collar, special size, orange		

Approvals

