

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









915CL -OPTICAL FIBER CLEAVER

Fast, Accurate and Reliable Fiber Cleaving

SPLICE AND CLEAVE FIBER THE RIGHT WAY!

FAST

Cleaved Fiber remains in the adapter ready to splice and is compatible with the 910FS or the lighter, 915FS model.

ACCURATE

Precision-engineered blades accurately cleave fibers for minimal loss.

RELIABLE

Field tested to perform the dust bin safely collects end cuts.



www.youtube.com/GreenleeDEMO

BENEFITS

- Accurate Cleaves. Cleave multi-mode and single-mode fiber optic cables.
- Long Life. Blades rotate for longer life over 48,000 cleaves.
- Adaptable. Supports 250um, 900um fibers and loose tube fibers.
- Fast. For use with the 910FS or the 915FS Optical Fusion Splicer for maximum speed and efficiency with auto return mechanism.
- Dust bin. Safely collects end cuts during cleaving process.
- Fixed Clamp. Allows the technician to use the 915CL as a standalone cleaver.

SPECIFICATIONS

APPLICABLE FIBERS	SM (G.652); MM (G.651); DS (G.653); NZDS (G.655); BIF (G.657)		
FIBER CLEAVED LENGTH	10mm		
CLADDING DIAMETER	125µm		
COATING DIAMETER	0.25 mm and 0.9 mm		
FIBER COUNT	Single		
CLEAVING ANGLE	≤ 1.5°		
BLADE LIFE	48,000 Cleaves		
WEIGHT	0.56 lbs (255 g)		
DIMENSIONS (HxWxD)	2.29 x 2.17 x 1.89" (58 x 55 x 48 mm)		



FOR USE WITH THE 910FS OR 915FS FUSION SPLICERS

ORDERING INFORMATION

CAT NO.	UPC NO.	DESCRIPTION
915CL	06864	915CL Optical Fiber Cleaver
01640	01640	Cleaving Wheel
915FS	06672	915FS Optical Fusion Splicer
01332	01332	250µm Adapter (Pair)
01333	01333	900µm Adapter (Pair)
05801	05801	Loose Tube Adapter (Pair)
03245	03245	3mm Adapter (Pair)

The 915CL is supplied with a fixed clamp and a mounting screw that the
technician can use to permanently mount the fixed clamp to the cleaver.
Shipped not assembled.

CAT NO.	UPC NO.	DESCRIPTION
PA1171	12225	ProGrip 5-in-1 Fiber Optic Stripper
PA1177	12228	ProGrip 3-in-1 Fiber Optic Stripper
10997	10997	Economy Fiber Optic Stripper
PA1511	03120	Kevlar Cutter
MSS100	05712	Mid Span Slitter
07111	07111	Fixed Clamp for 915CL with Screw







