

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








Molded RF Chokes

Special Features

- High Q, high reliability
- Iron or ferrite core
- Injection molded to protect coil from extreme environment
- Flame retardant coating
- Consistent body dimension
- Color band or numerical marking identification
- Dielectric strength 1000Vrms
- Operating temperature -55 to +105°C
- Current to cause 35°C maximum temperature rise



9210 Series						
Part Number	L (uH) ±5%	Q Min.	Test Freq. (MHz)	SRF (MHz) Min.	$egin{array}{c} {\sf DCR} \\ (\Omega) \\ {\sf Max}. \end{array}$	I, DC (mA)
9210-54	36	60	2.5	15.5	2.5	180
9210-56	39	60	2.5	14.5	2.6	176
9210-58	43	60	2.5	13.7	2.7	172
9210-60	47	55	2.5	13.0	2.75	170
9210-62	51	55	2.5	12.7	2.85	167
9210-64	56	55	2.5	12.0	3.0	164
9210-66	62	55	2.5	11.5	3.15	160
9210-68	68	55	2.5	11.0	3.3	156
9210-70	75	55	2.5	10.5	3.7	147
9210-72	82	50	2.5	10.3	3.9	143
9210-74	91	50	2.5	10.0	4.3	136
9210-76	100	50	2.5	9.5	4.5	133
9210-78	110	60	7.9	8.9	4.9	128
9210-80	120	65	7.9	8.7	5.2	124
9210-82	130	65	7.9	8.5	5.45	121
9210-84	150	65	7.9	8.0	6.05	114
9210-86	160	65	7.9	7.5	6.40	111
9210-88	180	65	7.9	7.0	6.75	108
9210-90	200	65	7.9	6.5	7.1	106
9210-92	220	65	7.9	6.2	7.45	103
9210-94	240	65	7.9	5.9	7.8	101