



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





GREENLEE.
A Textron Company

MADE FOR THE TRADE!™

METER, CALIBRATED LIGHT (93-172-C)

Digital Light Meter



Image
Unavailable

Cat No: 93-172-C

UPC No: 783310070849

Description

- Measures incandescent, fluorescent, metal halide, high-pressure sodium and halogen lamp output
- Color and cosine-corrected for enhanced accuracy
- Measures up to 50,000 lux
- Peak and data hold means no lost measurements
- Accessories included: (1) 9V battery and carrying case
- Lifetime Limited Warranty

Specifications

- Accuracy Incandescent Light Source : Plus Or Minus 4 PCT
- Accuracy Other Light Sources : Plus Or Minus 7 PCT
- Application : For Measures Incandescent, Fluorescent, Metal halide, High-Pressure Sodium And Halogen Lamp Output
- Foot Candles : 0.01 - 5000 FC (20/200/2000/5000)
- Includes : (1) 9V Battery And Carrying Case
- LUX : 0.1 - 50000 LUX (200/2000/20000/50000)
- Replacement Part : 06200 Carrying Case, 06061 Sensor, 06083 Sensor Case
- Sampling Rate : 2.5 Times Per Second
- Temperature Range : 0 - 40 DEG C (32 - 104 DEG F)
- Type : Digital, Calibrated