



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





USB MicroSD Card Reader/Writer - microSD / microSDHC / microSDXC

PRODUCT ID: 939



. Description

This is the cutest little microSD card reader/writer - but don't be fooled by its adorableness! It's wicked fast and supports up to 64 GB SDXC cards! Simply slide the card into the edge and plug it into your computer. No drivers are required, it shows up as a standard 'Mass Storage' device under any OS. You can swap cards while the USB port is kept plugged in.

Comes with a handy little cord so you can attach it to your datalogger project. Also has a little plastic cover for the USB A connector part so it won't short against nearby electronics.

Max read speed is 16 MB/sec, max write speed is 6 MB/sec - most microSD cards are not this fast so the bottleneck will be the card, not the reader

Does not come with a microSD card! We do carry microSD cards in the shop that go great with the reader.

• Technical Details

Reader Specifications:

- Dimensions — 0.984" x 0.478" x 0.104" (24.99mm x 12.14mm x 2.64mm)
- Operating Temperature — 0° to 60° C / 32° to 140° F
- Storage temperatures — -40° to 85° C / -40° to 185° F
- Weight — 0.137 oz (3.8g)

