

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Search Entire Site Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > > 952801 > 952801CFLF

Add to myIDT [?]

952801CFLF


() IDT.

Category:

Generic Part: 952801 PC CLOCK Market Group: Description: PC MAIN CLOCK

The ICS952801 is a two chip clock solution for desktop designs using SIS 755/760 style chipsets. When used with a zero delay buffer such as the ICS9179-16 for PC133 or the ICS93735 for DDR applications it provides all the necessary clocks signals for such a system. Output Features: • 2 - Pairs of differential push-pull K8CPU outputs • 8 - PČICLK @ 3.3V • 2 - AGPCLK @ 3.3V • 3 - REF @ 3.3V • 2 - ZCLK @ 3.3V • 1 - 24\_48MHz @ 3.3V

• 1 - 48MHz@3.3V



#### **Parameters**

Package	SSOP 48 (PVG48)
Speed	NA
Temperature	С
Voltage	3.3 V
Status	Active
Sample	Yes
Minimum Order Quantity	90
Factory Order Increment	30

#### **Distributor Inventory**

No Pricing information is available from our Distributors at this time.

### **Documents**

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

## **Package**

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temprature	260°C
Rebake Conditions	N/A
Length	15.9
Mark	PVG
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active