

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Search Entire Site

▶ GO

Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets >

Add to myIDT [?]

You may also like.

952909AKLF

Category: **Desktop Chipsets**

Generic Part: 952909 PC CLOCK Market Group: Description: PC MAIN CLOCK

ICS952909 is a 56 pin clock chip for VIA PT880/PM880 style chipsets. When used with a fanout DDR buffer, such as a style chipsets and the following properties of the properthe 93788, it provides all the necessary clock signals for such a system. Output Features: • 3 - 0.7V current-mode differential CPU pairs • 10 - PCI, 3 free running, 33MHz • 2 - REF, 14.318MHz • 3 - 3√66, 66.66MHz • 1 -

48MHz • 1 - 24/48MHz • 2 - 25MHz @ 2.5V



Parameters

Package	VFQFPN 56 (NLG56)	
Voltage	3.3 V	
Package	VFQFPN 56	
Speed	NA	
Temperature	С	
Status	Active	
Sample	Yes	
Minimum Order Quantity	260	
Factory Order Increment	260	

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Ш	Туре	Title	Size	Revision Date
	Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	VFQFP-N 8.0 X 8.0 X 0.9 MM - NO LEAD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	3
Category	Green
Moisture Exposure Floor Life	168 hrs. @ <30°C/60%RH
Peak Reflow Temprature	260°C
Rebake Conditions	48 hrs.@125°C
Length	8.0
Mark	K
Width	8.0
Pitch	0.5
Thickness	0.85
Status	Active