

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Contact IDT | Investors | Press

About IDT

Products

Support

myIDT

Calculators | Cross Reference | Green Initiative | Military | Parametric Search | Search by Part Number, Keyword, Document, Green/Pb-Free, Package

 $Home > Products > Clock / Timing \ Devices > PC-Notebook \cdot Server \ Clock \ Synthesizer \ by \ Chipset \ Vendor > Desktop \ Chipsets > 952926 > 952926CFLFT$

952926CFLFT

Category: Desktop Chipsets

Generic Part: 952926 PC CLOCK Market Group:

Description:

ICS952926 is a 48 pin clock chip for VIA VX/CX 700 style chipsets. When used with a fanout DDR buffer, such as the

93788, it provides all the necessary clock signals for such a system.

Output Features:• 3 - 0.7V current-mode differential CPU pairs

• 10 - PCI, 3 free running, 33MHz

• 2 - REF, 14.318MHz • 3 - 3V66, 66.66MHz

• 1 - 48MHz • 1 - 24/48MHz

• 2 - 25MHz, 2 free running @2.5V or 3.3V

You may also like.



Parameters

Temperature	С
Voltage	3.3 V
Package	SSOP 48
Speed	NA
Status	Active
Sam ple	Yes
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date	
Misc	PC Clocks Contact Info	61 KB	05/29/2007	

Package

Package	SSOP 48 (PVG48)
Description	SSOP 300 MIL
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	F
Package Type	SSOP
Lead Count	48
Length	15.9 mm
Width	7.5 mm
Thickness	2.3 mm
Pitch	0.64 mm
Tube / Tray	TUBE
Quantity per Tube/Tray	30
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	1
Moisture Exposure Floor Life	Unlimited@<30C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Related Package Documents	view documents