mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



NorComp Quick Reference Guide to D-Sub Backshells

	Material			Cable Entry							Hardware				Standard	High Density
											Standard		Other			
												4-40	Hardware			
	70db	60db									4-40 std.	thumb-	types	Strain	Connector	Connector
Series	Die Cast	Metalized	Plastic	180°	90°	60 °	45 °	40 °	35 °	3-way	screws	screws	available	Relief type	Size	Size
950		Х	Х			Х					Х		M3	Mechanical	9,15,25,37	15,26,44,62
951		Х	Х			Х						Х	M3	Mechanical	9,15,25,37	15,26,44,62
952	Х			Х								Х	M2.5-M3-M2.6	Mechanical	9,15,25,37	15,26,44,62
953	Х								Х			Х	M2.5-M3-M2.6	Mechanical	9,15,25,37	15,26,44,62
954	Х						Х						Slide Lock	Compression	9,15,25,37	15,26,44,62
955	Х	Х	Х							Х			Quick Lock	Mechanical	9,15,25,37	15,26,44,62
956		Х	Х	Х							Х			Compression	9, 15, 25	15,26,44
957		Х	Х	Х							Х			N/A	9,15,25, 9-to-25	15,26,44, 15-to-44
958			Х	Х							Female Scr	ew Locks		N/A	9, 15, 25	15,26,44
970	Х	Х	Х	Х								Х	Х	Compression	9,15,25,37	15,26,44,62
971	Х	Х	Х				Х					Х	Х	Compression	9,15,25,37	15,26,44,62
972			Х	Х								Х		Mechanical	9,15,25,37	15,26,44,62
973		Х	Х	Х								Х		Mechanical	9,15,25,37	15,26,44,62
974		Х	Х			Х						Х		Mechanical	9,15,25,37	15,26,44,62
975		Х	Х							Х		Х		Mechanical	9,15,25,37	15,26,44,62
976		Х	Х	Х							Х			Compression	9,15,25,37	N/A
977		Х	Х	Х							Х	Х		Mechanical	9,15,25,37,50	15,26,44,62,78
978		Х	Х	Х							Х	Х		Compression	9,15,25,37,50	15,26,44,62,78
979	Х	Х	Х	Х							Х	Х	Х	Compression	9,15,25,37,50	15,26,44,62,78
981	Х				Х						Х	Х		Compression	9,15,25	15,26,44
982		Х	Х	Х			Х				Х			Mechanical	9,15,25,37,50	15,26,44,62,78
983		Х	Х	Х							Х	Х		Mechanical	9,15,25,37,50	15,26,44,62,78
993		х	Х		Х							Х		Mechanical	9,25	15,44
994	Х			Х							Х			Mechanical	9,15,25	15,26,44

New

N	or	Comp E	Bac	kshell F	^P art Nu	mber	Key:
Serie	s F	Position	ns I	Material	RoHS	Color	Put-up
970		025	-	040	R	01	1
		Exam	ple	: 970-0	25-040	R011	

9 Pos. Standard & 15 Pos. High Density use 9 Pos. Backshells 15 Pos. Standard & 26 Pos. High Density use 15 Pos. Backshells 25 Pos. Standard & 44 Pos. High Density use 25 Pos. Backshells 37 Pos. Standard & 62 Pos. High Density use 37 Pos. Backshells 50 Pos. Standard & 78 Pos. High Density use 50 Pos. Backshells