



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PRODUCT NO. 95635-XXXXX	PUSH-ROD LOCATION		STAND-OFF HEIGHT DIM "L"	DIM "P"	DOUBLE - DECK HEADER 92821-XXX	(B) CLOSEST TO PCB	(C) FARTEST FROM PCB	MOUNTING STYLE TO PCB AND PUSH-ROD SIDE
	DECK CLOSEST TO PCB	DECK FARTHEST FROM PCB				EJECT MECHANISM 88644-XXXX	EJECT MECHANISM 94307-XXXX	
000CA	LEFT	RIGHT	0.0	2.8	92821-000	10CA	00CA	
020CA	LEFT	RIGHT	2.0	2.5	92821-040	12CA	00CA	
050CA	LEFT	RIGHT	5.0	2.8	57956-050	15CA	00CA	
100CA	RIGHT	LEFT	0.0	2.8	92821-000	00CA	10CA	
120CA	RIGHT	LEFT	2.0	2.5	92821-040	02CA	10CA	
150CA	RIGHT	LEFT	5.0	2.8	57956-050	05CA	10CA	
200CA	RIGHT	RIGHT	0.0	2.8	92821-000	00CA	00CA	
220CA	RIGHT	RIGHT	2.0	2.5	92821-040	02CA	00CA	
250CA	RIGHT	RIGHT	5.0	2.8	57956-050	05CA	00CA	
300CA	LEFT	LEFT	0.0	2.8	92821-000	10CA	10CA	
320CA	LEFT	LEFT	2.0	2.5	92821-040	12CA	10CA	
350CA	LEFT	LEFT	5.0	2.8	57956-050	15CA	10CA	
000CALF	LEFT	RIGHT	0.0	2.8	92821-000LF	10CA	00CA	
020CALF	LEFT	RIGHT	2.0	2.5	92821-040LF	12CA	00CA	
050CALF	LEFT	RIGHT	5.0	2.8	57956-050LF	15CA	00CA	
100CALF	RIGHT	LEFT	0.0	2.8	92821-000LF	00CA	10CA	
120CALF	RIGHT	LEFT	2.0	2.5	92821-040LF	02CA	10CA	
150CALF	RIGHT	LEFT	5.0	2.8	57956-050LF	05CA	10CA	
200CALF	RIGHT	RIGHT	0.0	2.8	92821-000LF	00CA	00CA	
220CALF	RIGHT	RIGHT	2.0	2.5	92821-040LF	02CA	00CA	
250CALF	RIGHT	RIGHT	5.0	2.8	57956-050LF	05CA	00CA	
300CALF	LEFT	LEFT	0.0	2.8	92821-000LF	10CA	10CA	
320CALF	LEFT	LEFT	2.0	2.5	92821-040LF	12CA	10CA	
350CALF	LEFT	LEFT	5.0	2.8	57956-050LF	15CA	10CA	




mat'l. code				surface ☒ ISO 1302 ☒ ISO 406 ISO1101		tolerance		projection		product family		
l t r e c n n o d r				date		tolerances unless otherwise specified				PCMCIA		
D	V61383	RDS	9/16/96	angle		0.X±0.3		MM		DOUBLE-DECK HEADER EJECT ASSY		
E	V11670	RGD	6/6/01	0°±2'		0.XX±0.13						
F	V20419	LP	3/25/02			0.XXX±0.051		scale 1:1				
G	N05-0052	WB	02/25/05	dr	D.SHEAFFER	9/16/96			dwg no		sheet 1 of 4	size
H	N05-0077	WB	03/17/05	engr	D.BRANN	9/16/96			95635		A4	
J	EX-N-007340	ZK	10/25/11	chr	D.BRANN	9/16/96			type		Product Customer Drawing	
K	EX-N-011443	ZK	04/12/12	appd	D.BRANN	9/16/96						
sheet	revision	K	K	K	K							
index	sheet	1	2	3	4							



PRODUCT NO. 95635-XXXX	PUSH-ROD LOCATION		STAND-OFF HEIGHT DIM "L"	DIM "P"	DOUBLE DECK HEADER 92821-XXX	B CLOSEST TO PCB EJECT MECHANISM 88644-XXXX	C FARTHEST FROM PCB EJECT MECHANISM 94307-XXXX	MOUNTING STYLE TO PCB AND PUSH-ROD SIDE
	DECK CLOSEST TO PCB	DECK FARTHEST FROM PCB						
500CA	RIGHT	LEFT	0.0	2.8	92821-500	10CA	00CA	
520CA	RIGHT	LEFT	2.0	2.5	92821-540	12CA	00CA	
550CA	RIGHT	LEFT	5.0	2.8	57956-550	15CA	00CA	
600CA	LEFT	RIGHT	0.0	2.8	92821-500	00CA	10CA	
620CA	LEFT	RIGHT	2.0	2.5	92821-540	02CA	10CA	
650CA	LEFT	RIGHT	5.0	2.8	57956-550	05CA	10CA	
700CA	RIGHT	RIGHT	0.0	2.8	92821-500	10CA	10CA	
700CP	RIGHT	RIGHT	0.0	2.8	92821-500	10CP	10CP	
720CA	RIGHT	RIGHT	2.0	2.5	92821-540	12CA	10CA	
750CA	RIGHT	RIGHT	5.0	2.8	57956-550	15CA	10CA	
800CA	LEFT	LEFT	0.0	2.8	92821-500	00CA	00CA	
820CA	LEFT	LEFT	2.0	2.5	92821-540	02CA	00CA	
850CA	LEFT	LEFT	5.0	2.8	57956-550	05CA	00CA	
500CALF	RIGHT	LEFT	0.0	2.8	92821-500LF	10CA	00CA	
520CALF	RIGHT	LEFT	2.0	2.5	92821-540LF	12CA	00CA	
550CALF	RIGHT	LEFT	5.0	2.8	57956-550LF	15CA	00CA	
600CALF	LEFT	RIGHT	0.0	2.8	92821-500LF	00CA	10CA	
620CALF	LEFT	RIGHT	2.0	2.5	92821-540LF	02CA	10CA	
650CALF	LEFT	RIGHT	5.0	2.8	57956-550LF	05CA	10CA	
700CALF	RIGHT	RIGHT	0.0	2.8	92821-500LF	10CA	10CA	
700CPLF	RIGHT	RIGHT	0.0	2.8	92821-500LF	10CP	10CP	
720CALF	RIGHT	RIGHT	2.0	2.5	92821-540LF	12CA	10CA	
750CALF	RIGHT	RIGHT	5.0	2.8	57956-550LF	15CA	10CA	
800CALF	LEFT	LEFT	0.0	2.8	92821-500LF	00CA	00CA	
820CALF	LEFT	LEFT	2.0	2.5	92821-540LF	02CA	00CA	
850CALF	LEFT	LEFT	5.0	2.8	57956-550LF	05CA	00CA	

NOTES (CONTINUOUS ON SHEET 3):
1 EJECT FORCE 3.5kg MAX.
2 EJECT TRAVEL - 8.0mm
3 MATERIAL
HOUSING: HIGH TEMPERATURE THERMOPLASTIC UL94V-0 BLACK
TERMINAL: COPPER ALLOY
COVER: STAINLESS STEEL
4 FINISH - PIN
UNDER PLATING: 1.27µm MIN. Ni
CONTACT AREA: 0.076 µm MIN. GOLD
SOLDER TAIL(TIN LEAD OPTION): 2.5µm MIN Sn-Pb
SOLDER TAIL(LEAD FREE OPTION): 2.5µm MIN PURE TIN

mat'l. code		surface		tolerance		projection		product family	
		ISO 1302		ISO 406 ISO 1101				PCMCIA	
l t r e c n n o d r		date		tolerances unless otherwise specified		title			
K				angle		MM		DOUBLE-DECK	
				0°±2'		scale 1:1		HEADER EJECT ASSY	
				dr D.SHEAFFER		9/16/96		dwg no	
				enr D.BRANN		9/16/96		sheet 2 of 4	
				chr D.BRANN		9/16/96		size	
				appd D.BRANN		9/16/96		A4	
sheet		revision						type	
index		sheet						Product Customer Drawing	





P/N: 95635-XXXCA/XXXCALF
BELOW P.C.B.
RIGHT/RIGHT PUSH-ROD
P.C.B. LAYOUT 2 (SHT. 3)
VIEW ROTATED 180°
PUSH-ROD & DECK ARE
AS VIEWED BY USER

NOTES (CONTINUOUS FROM SHEET 2):

DIM "X"	4.25±0.1	3.5±0.1	5.0±0.1
PIN NUMBER	OTHERS	36,67	1,17,34,35,51,68

- RECOMMENDED HOLD DOWN - 2mm SCREWS (95121)
RECOMMENDED SCREW TORQUE: 1.0 TO 1.5 MAX in-lbs. (1.2-1.7 cm-kgs).
- IF LEAD FREE P/N, THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.00MM MINIMUM THICK CIRCUIT BOARD.
- LEAD FREE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DISCRIBLED IN GS-22-008
- IF LEAD FREE P/N, PACKAGING MEETS GS-14-920 SPECIFICATION
- PRODUCT SPEC: 110-263

mat'l. code	surface	tolerance	projection	product family
	ISO 1302	ISO 406	ISO 1101	PCMCIA
l'tecn nodr date	tolerances unless otherwise specified			
K	angle	0.X±0.3	MM	DOUBLE-DECK HEADER EJECT ASSY
	0°±2'	0.XX±0.13	scale 1:1	
	0°±2'	0.XXX±0.051		
dr	D.SHEAFFER	9/16/96		dwg no
enr	D.BRANN	9/16/96		sheet3of4
chr	D.BRANN	9/16/96		size
appd	D.BRANN	9/16/96		A4
sheet	revision			type
index	sheet			Product Customer Drawing



NOTES:

1. ALL TOLERANCES $\pm$ 0.15 UNLESS NOTED.
2. RECOMMENDED DIAMETER IS ϕ 1.0 FOR PROCESSES USING PASTE REFLOW. HOLE MAY BE AS SMALL AS ϕ 0.79
3. BOARD VIEW FROM CONNECTOR MOUNTED SIDE TOP OF BOARD IN APPLICATION

mat'l. code				surface		tolerance		projection		product family											
				ISO 1302		ISO 406 ISO 1101				PCMCIA											
ltr		ecn		nodr		date		tolerances unless otherwise specified		title											
K								angle		0.X±0.3				DOUBLE-DECK HEADER EJECT ASSY							
								0°±2'		0.XX±0.13											
										0.XXX±0.051											
								dr		D.SHEAFFER		9/16/96				dwg no		sheet 4 of 4		size	
								enr		D.BRANN		9/16/96				95635		A4			
								chr		D.BRANN		9/16/96									
								appd		D.BRANN		9/16/96									
sheet		revision														type		Product Customer Drawing			
index		sheet																			