



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



ETD Cores (9595545402)

Part Number: 9595545402

95 ETD CORE SET

ETD cores have been designed to make optimum use of a given volume of ferrite material for maximum throughput power, specifically for forward converter transformers. The structure, which includes a round center post, approaches a nearly uniform cross- sectional area throughout the core and provides a winding area that minimizes winding losses. ETD cores are used mainly in switched- mode power supplies and permit off- line designs where IEC and VDE isolation requirements must be met.

☐ ETD cores can be supplied with the center post gapped to a mechanical dimension or an A_L value.

Weight indicated is per pair or set.

Weight: 180 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	54.2	± 1.00	2.134	—
B	27.1	± 0.30	1.067	—
C	18.9	± 0.40	0.744	—
D	19.5	± 0.30	0.768	—
E	40.5	min	1.594	min
F	18.9	± 0.30	0.744	—

Chart Legend

$\Sigma l / A$: Core Constant, l_e : Effective Path Length, A_e : Effective Cross- Sectional Area, V_e : Effective Core Volume

A_L : Inductance Factor ☐

Explanation of Part Numbers: Digits 1 & 2 = product class and 3 & 4 = material grade.

Electrical Properties	
A_L (nH)	6500 ±25%
A_e (cm ²)	2.65
$\Sigma l / A$ (cm ⁻¹)	4.7
l_e (cm)	12.56
V_e (cm ³)	33.3
A_{min} (cm ²)	2.4

A_L value is measured at 1 kHz, B < 10 gauss