



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



[Home](#) > [Products](#) > > 960008 > 960008AFLF

[Add to myIDT \[?\]](#)

You may also like...

960008AFLF

Category:
Generic Part: 960008

Market Group: PC CLOCK

Description: PC SPECIAL PURPOSE

Recommended Application: Ricoh Printer Application (Soriano) Output Features: $\hat{\text{a}}\text{€}\phi$ 2.5V - 3.3V power for GIGA/ASIC $\hat{\text{a}}\text{€}\phi$ Supports Spread Spectrum $\hat{\text{a}}\text{€}\phi$ 1 - Single-ended GIGACLK @ 125MHz $\hat{\text{a}}\text{€}\phi$ 1 - ASIC @ 33MHz $\hat{\text{a}}\text{€}\phi$ 1 - ASIC @ 80MHz - 133MHz $\hat{\text{a}}\text{€}\phi$ 1 - SDCLK @ 50MHz Features/Benefits: $\hat{\text{a}}\text{€}\phi$ Selectable SMBus address $\hat{\text{a}}\text{€}\phi$ Selectable output enable/disable via SMBus Key Specifications: $\hat{\text{a}}\text{€}\phi$ Clock jitter: <250ps $\hat{\text{a}}\text{€}\phi$ Operating current: <50mA (typical)

Parameters

Package	SSOP 28 (PYG28)
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	Yes
Minimum Order Quantity	94
Factory Order Increment	47

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 5.3 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Length	10.2
Mark	PYG
Width	5.3
Pitch	0.65
Thickness	1.73
Status	Active