

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Search Entire Site Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > > 960008 > 960008AFLFT

Add to myIDT [?]

You may also like.

960008AFLFT

DIDT.

Category:

Generic Part: 960008 PC CLOCK Market Group:

Description:

PC SPECIAL PURPOSE Recommended Application: Ricoh Printer Application (Soriano) Output Features: • 2.5V - 3.3V power for GIGA/ASIC • Supports Spread Spectrum • 1 - Single-ended GIGACLK @ 125MHz • 1 - ASIC @ 33MHz • 1

- ASIC @ 80MHz - 133MHz • 1 - SDCLK @ 50MHz Features/Benefits: • Selectable SMBus address • Selectable output enable/disable via SMBus Key Specifications: • Clock jitter: <250ps • Operating current:

<50mA (typical)



Parameters

| Package | SSOP 28 (PYG28) |
|-------------------------|-----------------|
| Speed | NA |
| Temperature | С |
| Voltage | 3.3 V |
| Status | Active |
| Sample | No |
| Minimum Order Quantity | 1000 |
| Factory Order Increment | 1000 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Туре | Title | Size | Revision Date |
|------|------------------------|-------|---------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 |

Package

| Description | SSOP 5.3 MM |
|----------------------------------|-----------------------------|
| Class | PLASTIC |
| Moisture Sensitivity Level (MSL) | 1 |
| Category | Green |
| Moisture Exposure Floor Life | Unlimited @ <30°C/85% RH |
| Peak Reflow Temprature | 260°C |
| Rebake Conditions | N/A |
| Length | 10.2 |
| Mark | PYG |
| Width | 5.3 |
| Pitch | 0.65 |
| Thickness | 1.73 |
| Status | Active |