



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Intel® Core™ i5 Processor I5-660

Processor Specifications:

sSpec Number:	SLBLV	Package Type:	LGA1156
CPU Speed:	3.33 GHz	Manufacturing Technology:	32 nm
PCG:	09A	Core Stepping:	C2
Bus Speed:		CPUID String:	20652h
Bus/Core Ratio:	25	Thermal Design Power:	73W
L3 Cache Size:	4 MB	Thermal Specification:	72.6°C
L3 Cache Speed:		VID Voltage Range:	.65V-1.400V

Product Documentation:

<http://www.intel.com/design/corei5/documentation.htm>

Product Order Codes:

Box Order Code: BXC80616I5660
BX80616I5660

OEM Order Code: CM80616003177AC

Supported Features:

- Dual Core
- Enhanced Intel Speedstep® Technology
- Hyper-Threading Technology ¹
- Intel® EM64T ²
- Intel® Virtualization Technology
- Enhanced Halt State (C1E)
- Execute Disable Bit ³

Notes:

This part supports Intel® HD Graphics.

The integrated graphics frequency is 733 MHz.

This part supports DDR3 memory speeds up to 1333 MHz.

Intel SSE4.1 and SSE4.2 enabled.

Intel® AES-NI enabled.

Intel® Virtualization Technology for Directed I/O (Intel® VT-d) enabled.

These parts have Intel® Trusted Execution Technology (Intel® TXT) enabled.

Max Intel® Turbo Boost Technology Frequency (GHz): 2 core: 3.46 GHz, 1 core: 3.60 GHz