



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# Intel® Xeon® Silver 4114T Processor

13.75M Cache, 2.20 GHz

Spec Code

SR3MM

Ordering Code

CD8067303645300

## Intel® Xeon® Silver 4114T Processor (13.75M Cache, 2.20 GHz)

Code Name	Skylake
-----------	---------

### **Essentials**

Vertical Segment	Server
Processor Number	4114T
Status	Launched
Launch Date	Q3'17
Lithography	14 nm
Recommended Customer Price	\$773.00

### **Performance**

# of Cores	10
# of Threads	20
Processor Base Frequency	2.20 GHz
Max Turbo Frequency	3.00 GHz
Cache	13.75 MB L3
# of UPI Links	2
TDP	85 W

### **Supplemental Information**

Embedded Options Available	Yes
Conflict Free	Yes
Datasheet	<a href="#">Link</a>
Product Brief	<a href="#">Link</a>

### **Memory Specifications**

Max Memory Size (dependent on memory type)	768 GB
--	--------

Memory Types	DDR4-2400
Maximum Memory Speed	2400 MHz
Max # of Memory Channels	6
ECC Memory Supported ‡	Yes
<b>Expansion Options</b>	
Scalability	2S
PCI Express Revision	3
Max # of PCI Express Lanes	48
<b><u>Package Specifications</u></b>	
Sockets Supported	FCLGA3647
T <sub>CASE</sub>	92°C
Package Size	76.0mm x 56.5mm
Low Halogen Options Available	See MDDS
<b><u>Advanced Technologies</u></b>	
Intel® Optane™ Memory Supported ‡	No
Intel® Speed Shift Technology	Yes
Intel® Turbo Boost Max Technology 3.0 ‡	No
Intel® Turbo Boost Technology	2
Intel® vPro™ Technology ‡	Yes
Intel® Hyper-Threading Technology ‡	Yes
Intel® Virtualization Technology (VT-x) ‡	Yes
Intel® TSX-NI	Yes
Intel® 64 ‡	Yes
Instruction Set Extensions	Intel® SSE4.2, Intel® AVX, Intel® AVX2, Intel® AVX-512
# of AVX-512 FMA Units	1
Enhanced Intel SpeedStep® Technology	Yes
Intel® Volume Management Device (VMD)	Yes
<b><u>Security &amp; Reliability</u></b>	
Intel® AES New Instructions	Yes
Intel® Trusted Execution Technology ‡	Yes
Execute Disable Bit ‡	Yes
Mode-based Execute Control (MBE)	Yes