



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China




[Compare Queue \(0\)](#)
[Send Feedback](#)
[English](#)
[Home](#)
[Intel® Processors](#)
[Intel® Xeon® Processor E3 Family](#)
[Intel® Xeon® Processor E3-1200 Series](#)


Intel® Xeon® Processor E3-1275V2 (8M Cache, 3.50 GHz)

SPECIFICATIONS


[All](#)
[Essentials](#)
[Memory Specifications](#)
[Graphics Specifications](#)
[Expansion Options](#)
[Package Specifications](#)
[Advanced Technologies](#)

COMPATIBLE PRODUCTS

[ORDERING / SSPECS / STEPPINGS](#)











Specifications

Essentials

Status	Launched
Launch Date	Q2'12
Processor Number	E3-1275V2
# of Cores	4
# of Threads	8
Clock Speed	3.5 GHz
Max Turbo Frequency	3.9 GHz
Intel® Smart Cache	8 MB
Bus/Core Ratio	35
DMI	5 GT/s
Instruction Set	64-bit
Instruction Set Extensions	AVX, SSE4.1, SSE4.2
Embedded Options Available	 Yes
Lithography	22 nm
Max TDP	77 W
Recommended Customer Price	TRAY: \$339 BOX : \$350

Memory Specifications

Max Memory Size (dependent on memory type)	32 GB
Memory Types	DDR3-1333/1600
# of Memory Channels	2

Max Memory Bandwidth	25.6 GB/s
*Trademarks	
ECC Memory Supported	 Yes
Graphics Specifications	
Processor Graphics	 Intel® HD Graphics P4000
Graphics Base Frequency	650 MHz
Graphics Max Dynamic Frequency	1.25 GHz
Intel® Quick Sync Video	Yes
Intel® InTru™ 3D Technology	Yes
Intel® Flexible Display Interface (Intel® FDI)	Yes
Intel® Clear Video HD Technology	Yes
Dual Display Capable	Yes
# of Displays Supported	 3
Expansion Options	
PCI Express Revision	3.0
PCI Express Configurations	 1x16 & 1x4, 2x8 & 1x4 or 1x8 & 3x4
Package Specifications	
Max CPU Configuration	1
Package Size	37.5mm x 37.5mm
Sockets Supported	FCLGA1155
Low Halogen Options Available	See MDDS
Advanced Technologies	
Intel® Turbo Boost Technology	2.0
Intel® vPro Technology	Yes
Intel® Hyper-Threading Technology	 Yes
Intel® Virtualization Technology (VT-x)	 Yes
Intel® Virtualization Technology for Directed I/O (VT-d)	 Yes
Intel® Trusted Execution Technology	 Yes
AES New Instructions	 Yes
Intel® 64	 Yes

"Announced" SKUs are not y availability.

The Recommended Custom are for direct Intel customers etc. not included. Prices may special promotional arranger formal pricing offer from Intel obtain a formal price quotatic

"Intel classifications" consist Harmonized Tariff Schedule without recourse to Intel and regarding the proper ECCN (such, your company is respo the time of export.

Intel processor numbers are differentiate features within e See <http://www.intel.com/pro>

Hyper-Threading Technology processor supporting HT Tec operating system. Performan you use. See www.intel.com/ including details on which pr

64-bit computing on Intel® ai chipset, BIOS, operating sys architecture. Processors will architecture-enabled BIOS. F software configurations. Con


Max Turbo Frequency refers with Intel® Turbo Boost Tech Boost Technology capability. on hardware, software, and c on whether your system deliv www.intel.com/technology/tu

Enabling Execute Disable Bit Disable Bit capability and a s on whether your system deliv

Intel® Virtualization Technol BIOS, virtual machine monit for it. Functionality, performa software configurations. Intel currently in development.

System and Maximum TDP i not all I/Os for chipsets are u

All information provided is su changes to manufacturing lif without notice. The informati

Idle States		Yes
Enhanced Intel SpeedStep® Technology		Yes
Intel® Demand Based Switching		Yes
Thermal Monitoring Technologies		Yes
Intel® Fast Memory Access		Yes
Intel® Flex Memory Access		Yes
Execute Disable Bit		Yes
Intel® VT-x with Extended Page Tables (EPT)		Yes

representations or warranties product features, availability, contact system vendor for m

Low Halogen: Applies only to and PVC in the final product. finished assembly meet JS-7 21 requirements. The replace better for the environment.

Some products can support , particular, i7-2630QM/i7-263 -2415M. Please contact OEM update.

©Intel
Corporation



Compare Queue (0)

Send Feedback

English

Type Here to Search Products

Home

Intel® Processors

Intel® Xeon® Processor E3 Family

Intel® Xeon® Processor E3-1200 Series

E3-1275V2



Intel® Xeon® Processor E3-1275V2 (8M Cache, 3.50 GHz)

SPECIFICATIONS

COMPATIBLE PRODUCTS

ORDERING / SSPECS / STEPPINGS

All

Ordering / sSpecs / Steppings

Retired and Discontinued

ORDERING AND SPEC INFORMATION

Ordering and Spec Information

Intel® Xeon® Processor E3-1275V2 (8M Cache, 3.50 GHz) FC-LGA12C, Tray

Socket	Step	Step TDP	Ordering Code	Spec Code	VT-x	ECCN	CCATS	US HTS	RCP
FCLGA1155	E1	77 W	CM8063701098702	SR0PA	Yes	5A992C	G077159	8542310000-HYBRD	\$339

Boxed Intel® Xeon® Processor E3-1275V2 (8M Cache, 3.50 GHz) FC-LGA12C

Socket	Step	Step TDP	Ordering Code	Spec Code	VT-x	ECCN	CCATS	US HTS	RCP
FCLGA1155	E1	77 W	BX80637E31275V2	SR0PA	Yes	5A992C	G077159	8542310000-HYBRD	\$350

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

The Recommended Customer Price ("RCP") is pricing guidance for Intel products. Prices are for direct Intel customers and are subject to change without notice. Taxes and shipping, etc. not included. Prices may vary for other package types and shipment quantities, and special promotional arrangements may apply. Listing of these RCP does not constitute a formal pricing offer from Intel. Please work with your appropriate Intel representative to obtain a formal price quotation.

"Intel classifications" consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company may be the exporter of record, and as such, your company is responsible for determining the correct classification of any item at the time of export.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products/processor_number for details.

Hyper-Threading Technology (HT Technology) requires a computer system with an Intel® processor supporting HT Technology and an HT Technology enabled chipset, BIOS and operating system. Performance will vary depending on the specific hardware and software you use. See www.intel.com/products/ht/hyperthreading_more.htm for more information including details on which processors support HT Technology.

64-bit computing on Intel® architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more information.

Max Turbo Frequency refers to the maximum single-core frequency that can be achieved with Intel® Turbo Boost Technology, which requires a PC with a processor with Intel Turbo Boost Technology capability. Intel Turbo Boost Technology performance varies depending on hardware, software, and overall system configuration. Check with your PC manufacturer on whether your system delivers Intel Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

Enabling Execute Disable Bit functionality requires a PC with a processor with Execute Disable Bit capability and a supporting operating system. Check with your PC manufacturer on whether your system delivers Execute Disable Bit functionality.

Intel® Virtualization Technology requires a computer system with a processor, chipset, BIOS, virtual machine monitor (VMM) and for some uses, certain platform software, enabled for it. Functionality, performance or other benefit will vary depending on hardware and software configurations. Intel Virtualization Technology-enabled VMM applications are currently in development.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Low Halogen: Applies only to brominated and chlorinated flame retardants (BFRs/CFRs) and PVC in the final product. Intel components as well as purchased components on the finished assembly meet JS-709 requirements, and the PCB / substrate meet IEC 61249-2-21 requirements. The replacement of halogenated flame retardants and/or PVC may not be better for the environment.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

*Trademarks

©Intel Corporation