



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# 96PR-152-UXH-D

**300 dpi Desktop Barcode Printer, 4.17",  
6 ips, USB/Serial/Ethernet/USB Host,  
SD Card Slot**



## Features

- 4" desktop barcode label printer
- Resolution: 300 dpi
- Max. print speed: 152mm (6")/sec
- USB, Serial, Ethernet, USB Host
- 128 MB Flash memory and 128 MB SDRAM memory
- microSD Flash memory expansion up to 32 GB

## Specifications

<b>Resolution</b>	12 dots/mm (300 dpi)
<b>Printing method</b>	Thermal Transfer & Direct Thermal
<b>Max. print speed</b>	152 mm (6")/second
<b>Max. print width</b>	106 mm (4.17")
<b>Max. print length</b>	11,430 mm (450")
<b>Enclosure</b>	Clamshell with double-walled plastic
<b>Physical dimension (W x H x D)</b>	226 x 198 x 332 mm (8.90" x 7.80" x 13.07")
<b>Weight</b>	3.75 kg (8.27 lbs)
<b>Label roll capacity</b>	127 mm (5") OD
<b>Ribbon</b>	300 m long, max. OD 67 mm, 1" core (ink coated outside)
<b>Ribbon width</b>	40 – 110 mm (1.6" – 4.3")
<b>Processor</b>	32-bit RISC CPU
<b>Memory</b>	<ul style="list-style-type: none"> <li>• 128 MB Flash memory</li> <li>• 128 MB SDRAM</li> <li>• microSD card reader for Flash memory expansion, up to 32 GB</li> </ul>
<b>Interface</b>	<ul style="list-style-type: none"> <li>• USB 2.0</li> <li>• Internal Ethernet, 10/100 Mbps</li> <li>• Centronics (option)</li> <li>• Slot-in 802.11 a/b/g/n wireless (option)</li> <li>• RS-232</li> <li>• USB Host</li> <li>• External Bluetooth (option)</li> </ul>
<b>Operation switch, button, LED/LCD</b>	<ul style="list-style-type: none"> <li>• 1 power switch</li> <li>• 1 feed/pause button</li> <li>• LED panel with 8 big icons</li> </ul>
<b>Power</b>	External universal switching power supply <ul style="list-style-type: none"> <li>• Input: AC 100-240V, 2.5A, 50-60Hz</li> <li>• Output: DC 24V, 3.75A, 90W</li> </ul>
<b>Sensors</b>	<ul style="list-style-type: none"> <li>• Transmissive gap sensor</li> <li>• Ribbon encode sensor</li> <li>• Black mark reflective sensor (position adjustable)</li> <li>• Head open sensor</li> </ul>
<b>Real time clock</b>	Factory Option
<b>Internal fonts</b>	<ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>
<b>Bar code</b>	<ul style="list-style-type: none"> <li>• 1D bar code               <ul style="list-style-type: none"> <li>Code 39, Code 93, Code128UCC, Code128 subsets A,B,C, Codabar, Interleaved 2 of 5, EAN 8, EAN 13, EAN 128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China post, ITF14, EAN14, Code 11, TELEPEN, TELEPENN, PLANET, Code 49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS</li> </ul> </li> <li>• 2D bar code               <ul style="list-style-type: none"> <li>TLC39, CODABLOCK F mode, PDF-417, Maxicode, DataMatrix, QR code, Aztec, Micro PDF 417, GS1 DataBar (RSS barcode)</li> </ul> </li> </ul>
<b>Font and barcode rotation</b>	0, 90, 180, 270 degree
<b>Printer language</b>	TSPL-EZTM (Compatible to EPL, ZPL, ZPL II)
<b>Media type</b>	Continuous, die-cut, black mark, fan-fold, notch (outside wound)
<b>Media width</b>	19 – 112 mm (0.75" – 4.4")
<b>Media thickness</b>	0.055 – 0.254 mm (2.17 – 10 mil)
<b>Media core diameter</b>	25.4 – 38.1 mm (1" – 1.5")
<b>Label length</b>	3 – 11,430 mm (0.1" – 450")
<b>Environment condition</b>	Operation: 5 – 40°C, 25 – 85% non-condensing Storage: -40 – 60°C, 10 – 90% non-condensing
<b>Safety regulation</b>	FCC Class B, CE Class B, RCM, UL, cUL, TÜV/Safety, CCC, BIS, EAC, ENERGY STAR®
<b>Environmental concern</b>	Comply with RoHS, WEEE
<b>Accessories</b>	<ul style="list-style-type: none"> <li>• Windows labeling software CD disk</li> <li>• USB cable</li> <li>• External universal switching power supply</li> <li>• Quick start guide</li> <li>• Power cord</li> </ul>
<b>Options</b>	<ul style="list-style-type: none"> <li>• Centronics parallel interface</li> <li>• 3.5" color TFT display (includes real time clock)</li> <li>• Peel-off module</li> <li>• 802.11 a/b/g/n wireless module (slot-in)</li> <li>• External label roll mount</li> <li>• KU-007 Plus programmable smart keyboard</li> <li>• Real time clock</li> <li>• Ribbon end sensor</li> <li>• Guillotine cutter (full cut)</li> <li>• Bluetooth module (serial interface)</li> <li>• KP-200 Plus keyboard display unit</li> </ul>

## Ordering Information

Part Number	Description
96PR-152-UXH-D	Desktop Barcode Printer, 300dpi, 4.17", 6 ips, USB/Serial/Ethernet/USB Host, SD card slot, US power cord
96PR-152-UXH-D-E	Desktop Barcode Printer, 300dpi, 4.17", 6 ips, USB/Serial/Ethernet/USB Host, SD card slot, EU power cord
96PR-152-UXH-D-C	Desktop Barcode Printer, 300dpi, 4.17", 6 ips, USB/Serial/Ethernet/USB Host, SD card slot, CN power cord