



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# 96PR-356-UXP-H-I

## 203 dpi Industrial Barcode Printer, 4.09", 14 ips, USB/Serial/Ethernet/Parallel/USB Host, SD Card Slot



### Features

- 4" industrial barcode label printer
- Resolution: 203 dpi
- Max. print speed: 356mm (14")/sec
- USB, Serial, Ethernet, Parallel, USB Host
- 128 MB Flash memory and 128 MB SDRAM memory
- microSD Flash memory expansion up to 32 GB

### Specifications

<b>Resolution</b>	8 dots/mm (203 dpi)	
<b>Printing method</b>	Thermal Transfer & Direct Thermal	
<b>Max. print speed</b>	356 mm (14")/second	
<b>Max. print width</b>	104 mm (4.09")	
<b>Max. print length</b>	25,400 mm (1,000")	
<b>Enclosure</b>	Die-cast aluminum base and frame/ Metal cover with two hinges & large clear media view window	
<b>Physical dimension (W x H x D)</b>	270 x 308 x 505 mm (10.63" x 12.13" x 19.88")	
<b>Weight</b>	15 kg (33.07 lbs)	
<b>Label roll capacity</b>	208.3 mm (8.2") OD	
<b>Ribbon</b>	600 m long, max. OD 90 mm, 1" core (ink coated outside or inside)	
<b>Ribbon width</b>	25.4 – 114.3 mm (1" – 4.5")	
<b>Processor</b>	32-bit RISC CPU	
<b>Memory</b>	<ul style="list-style-type: none"> <li>• 128 MB Flash memory (option 512 MB)</li> <li>• 128 MB SDRAM (option 256 MB)</li> <li>• SD Flash memory card reader for Flash memory expansion, up to 32 GB</li> </ul>	
<b>Interface</b>	<ul style="list-style-type: none"> <li>• RS-232</li> <li>• USB 2.0</li> <li>• USB host, for scanner or PC keyboard</li> <li>• Bluetooth (option)</li> </ul>	<ul style="list-style-type: none"> <li>• Centronics</li> <li>• Internal Ethernet, 10/100 Mbps</li> <li>• GPIO (option)</li> </ul>
<b>Power</b>	Internal switching power supply • Input: AC 100-240V, 2A, 50-60Hz • Output: DC 24V, 5A, 120W	
<b>LCD</b>	Graphic type, 128 x 64 pixel, with back light	
<b>Operation switch, button, LED</b>	1 power switch, 6 operation buttons (Menu, Pause, Feed, Up, Down, Select) & 3 LEDs	
<b>Sensors</b>	<ul style="list-style-type: none"> <li>• Gap transmissive sensor (position adjustable)</li> <li>• Head open sensor</li> <li>• Ribbon end sensor</li> </ul>	<ul style="list-style-type: none"> <li>• Black mark reflective sensor (position adjustable)</li> <li>• Ribbon encoder sensor</li> </ul>
<b>Real time clock</b>	Standard	
<b>Internal fonts</b>	<ul style="list-style-type: none"> <li>• 8 alpha-numeric bitmap fonts</li> <li>• Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font</li> </ul>	
<b>Bar code</b>	<ul style="list-style-type: none"> <li>• 1D bar code</li> <li>• Code 39, Code 93, Code 128UCG, Code 128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPCA-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Logmars</li> <li>• 2D bar code</li> <li>• PDF-417, Maxicode, DataMatrix, QR code, Aztech</li> </ul>	
<b>Font and barcode rotation</b>	0, 90, 180, 270 degree	
<b>Printer language</b>	TSPL-EZ (Compatible to EPL, ZPL, ZPL II)	
<b>Media type</b>	Continuous, die-cut, fan-fold, tag, notched, black mark, perforated, care label (outside wound)	
<b>Media width</b>	25.4 – 116 mm (1" – 4.5")	
<b>Media thickness</b>	0.06 – 0.30 mm (2.36 – 11.81 mil)	
<b>Media core diameter</b>	25.4 – 76.2 mm (1" – 3")	
<b>Label length</b>	5 – 25,400 mm (0.20" – 1,000")	
<b>Environment condition</b>	Operation: 5 – 40°C, 20 – 85% non-condensing Storage: -40 – 60°C, 5 – 90% non-condensing	
<b>Safety regulation</b>	FCC Class A, CE Class A, C-Tick Class A, UL, CUL, TÜV/Safety, CCC, CB	
<b>Environmental concern</b>	Comply with RoHS, WEEE	
<b>Accessories</b>	<ul style="list-style-type: none"> <li>• Windows labeling software CD disk</li> <li>• USB cable</li> </ul>	<ul style="list-style-type: none"> <li>• Quick start guide</li> <li>• Power cord</li> </ul>
<b>Options</b>	<ul style="list-style-type: none"> <li>• GPIO interface</li> <li>• Internal rewinding kit (Max. 6" OD)</li> <li>• Bluetooth module (serial interface)</li> <li>• Heavy duty cutter (rotary cutter)</li> <li>• High speed cutter</li> <li>• KU-007 Plus programmable smart keyboard</li> </ul>	<ul style="list-style-type: none"> <li>• Mainboard with extended memory (512 MB Flash/256 MB SDRAM)</li> <li>• Peel-off kit</li> <li>• Regular cutter (full cut guillotine cutter)</li> <li>• Care label cutter (rotary cutter)</li> <li>• KP-200 Plus keyboard display unit</li> </ul>

### Ordering Information

Part Number	Description
96PR-356-UXP-H-I	Industrial Barcode Printer, 203dpi, 4.09", 14 ips, USB/Serial/Ethernet/Parallel/USB Host, SD card slot, US power cord
96PR-356-UXP-H-E	Industrial Barcode Printer, 203dpi, 4.09", 14 ips, USB/Serial/Ethernet/Parallel/USB Host, SD card slot, EU power cord
96PR-356-UXP-H-C	Industrial Barcode Printer, 203dpi, 4.09", 14 ips, USB/Serial/Ethernet/Parallel/USB Host, SD card slot, CN power cord