

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Calculators | Cross Reference | Green Initiative | Military | Parametric Search | Search by Part Number, Keyword, Document, Green/Pb-Free, Package

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Notebook Chipsets > 9LPR600 > 9LPR600CGLFT

9LPR600CGLFT

Category: Notebook Chipsets

Generic Part: 9LPR600 Market Group: PC CLOCK

Description: SIS 662 MAIN CLOCK

Low Power Main Clock for SiS 662 style chipset

Output Features:

- 1 pair of differential push-pull CPU outputs
- 1 pair of differential push-pull CPU outputs, free-running
- 4 0.7V differential PCIEX pairs
- 2 0.7V differential PCIEX_F pairs, free-running
- 1 0.7V differential SATA pair
- 6 PCI (33MHz)
- 2 PCI (33MHz), free-running
- 1 24/48MHz selectable output
- 2-ZCLK
- 2 REF, 14.318MHz
- 1 12MHz output

You may also like.

Time is money

Parameters

Temperature	С
Voltage	3.3 V
Package	TSSOP 56
Speed	NA
Status	Active
Sample	Yes
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Datasheet	954201 Datasheet	163 KB	03/27/2006
	954204 Datasheet	200 KB	03/27/2006
	954321 Datasheet	225 KB	03/27/2006
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Package	TSSOP 56 (PAG56)
Description	TSSOP 6.1 MM 0.5MM PITCH
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	G
Package Type	TSSOP
Lead Count	56
Length	14.0 mm
Width	6.1 mm
Thickness	1.0 mm
Pitch	0.5 mm
Tube / Tray	TUBE
Quantity per Tube/Tray	34
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	1
Moisture Exposure Floor Life	Unlimited@<30C/85%RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Related Package Documents	view documents