



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Integrated Device Technology

The Analog and Digital Company™



[Products](#) |
 [Applications](#) |
 [Search](#) |
 [Support](#) |
 [Investor](#) |
 [About IDT](#)

[Power Management Solutions](#) |
 [Applications](#) |
 [Desktop](#) |
 [9P62000](#) |
 [9P62000NLG](#)

9P62000NLG

[Description](#) |
 [Parameters](#) |
 [Package](#) |
 [Distributor Inventory](#) |
 [Contacts](#)

Customer Support / Technical Support

DESCRIPTION

4 PHASE PWM CONTROLLER

Generic Part:

9P62000

Category:

Desktop

PARAMETERS

Package VFQFPN 64
Spec VR11.1
Phase 3 - 4
Integrated Driver Y or N or 3
Input Voltage 5V / 12V
Temperature C

PACKAGE

Package VFQFPN 64 (NLG64)
Description VFQFP-N 9.0 X 9.0 X 0.9 MM - NO LEAD
Status Active
Class PLASTIC
Category Green
Pb (Lead) Free Yes
Pb Free Category e3 Sn
Mark NLG
Package Type VFQFPN
Lead Count 64
Length 9.0 mm
Width 9.0 mm
Thickness 0.9 mm
Pitch 0.5 mm
Tube / Tray TRAY
Quantity per Tube/Tray 207
Quantity per Reel 3000
Moisture Sensitivity Level (MSL) 3
Moisture Exposure Floor Life 168hrs@<30C/60% RH
Peak Reflow Temperature 260°C
Rebake Conditions 48hrs@125C
Related Package Documents [view documents](#)

DISTRIBUTOR INVENTORY

Part	Distributor	Qty	Date	RFQ	Order
No matches found.					

CONTACTS

Sales Offices

► [Sales Offices and authorized distributors](#)

Technical Support

ASSP Computing

► [WWW: Clock Help](#)