

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Calculators | Cross Reference | Green Initiative | Military | Parametric Search | Search by Part Number, Keyword, Document, Green/Pb-Free, Package

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > DDR I and DDR II Buffers > Fan-out Buffers > 9P956 > 9P956AFLF

9P956AFLF

Fan-out Buffers Category:

Generic Part: 9P956

PC CLOCK Market Group: PC BUFFER Description:

DDR II fanout buffer for VIA Chipset

Output Features:

. Low skew, fanout buffer

• I2C for functional and output control

• Single bank 1-6 differential clock distribution

1 pair of differential feedback pins for input to output synchronization

• Supports up to 2 DDR DIMMs

• 400MHz (DDRII 800) output frequency support

• Programmable skew through SMBus

• Frequency defect control thorugh SMBus

• Individual output control programmable through SMBus

You may also like.



Parameters

Temperature	С
Voltage	3.3 V
Package	SSOP 28
Speed	NA
Status	Active
Sample	Yes
Minimum Order Quantity	141
Factory Order Increment	47

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Package	SSOP 28 (PYG28)
Description	SSOP 5.3 MM
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	F
Package Type	SSOP
Lead Count	28
Length	10.2 mm
Width	5.3 mm
Thickness	1.73 mm
Pitch	0.65 mm
Tube / Tray	TUBE
Quantity per Tube/Tray	47
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	1
Moisture Exposure Floor Life	Unlimited@<30C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Related Package Documents	view documents