



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



1

2

3

4

5

6

7

A

A XX-LC-TT





CKT: 06, 08, 14, 16, 18, 20

CKT: 24, 28, 32, 40

A XX-LC/7-T




CKT: 24, 28

B






B

C



C

D



D

E

CKT	A±0.20	B±0.20
06	7.62	5.08
08	10.16	7.62
14	17.78	15.24
16	20.32	17.78
18	22.86	20.32
20	25.40	22.86

CKT	A±0.20	B±0.20
24	30.48	27.94
28	35.56	33.02
32	40.64	38.10
40	50.80	48.26

CKT	A±0.20	B±0.20
24	30.48	27.94
28	35.56	33.02

E

F

Insulator : PBT-4830 , UL 94V-0

SPECIFICATIONS:

Current Rating : 1A

Dielectric withstanding Voltage : 1000V RMS/minute

Insulator resistance : 5000 Megohms min.

Contact resistance : 20 milliohms initial
30 milliohms after test.

Operating temperatures : -55°c to 85°c

Insertion force : 340g (12 oz) max.per contact.

Withdrawal force : 80g(2.82 oz) min.per contact

④ Soldering temperature: +245° C , 5S max.

F

RoHS compliant

Unit: mm

Scale Free

TOLERANCE

X. ±X

X.X ±X

X.XX ±X

DIM TOL

X. ° ±X°

X.X° ±X°

Angle TOL

Customer-No.

Date

Name

ASSMANN WSW-No.

A XX-LC-TT
A XX-LC/7-T

Drawing-No.

ASS 0810 CO rev04



Replace ASS 0333A CO
ASS 0333B CO

Sheet

1

2

3

4

5

6

7

H

G

A