

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







REVISIONS NOTES: THIRD ANGLE PROJ. 🕀 🖯 DESCRIPTION DATE REV I. MATERIALS AND FINISHES: RELEASE TO MFG 5/18/07 HOUSING: LCP (UL94V-0) CENTER CONTACT: BRASS, GOLD PLATE ADDED PURCHASING DRAWING, TAPE SPACING HALVED 11/10/14 GROUND CONTACT: PHOSPHOR BRONZE, SILVER PLATE 2. ELECTRICAL: A: IMPEDENCE:  $50\Omega$ , NOMINAL B: FREQUENCY RANGE: 0.045 GHz-3GHz (VSWR I.3 MAX.) 3-6 GHz (VSWR I.35 MAX) C. OPERATING VOLTAGE: 500 VRMSD. CONTACT RESISTANCE: CENTER CONTACT= 20 mΩ MAX. OUTER CONTACT =  $10m\Omega$  MAX. E. DIELECTRIC WITHSTANDING VOLTAGE: 200 VAC FOR I MINUTE. CURRENT LEAKAGE 2mA MAX. F. INSULATION RESISTANCE: 500 MEGOHMS MIN. SCALE 15.000 3. PHYSICAL: ー 0.3±0.Ⅰ A. DURABILITY: 20 CYCLES B. TEMPERATURE RANGE: -40°C TO +90°C — 4±0.∣ C. AMMC INTERFACE IS FULLY COMPATIBLE WITH "W.FL" SERIES PRODUCT. D. SUITABLE FOR LEAD-FREE SOLDER REFLOW PROCESS PER 349-50712. 2±0.1 ──► **├---** 2.6±0.05 **---**1.4±0.05 **├**─

- 0.3±0.Ⅰ

.7±0.15

 $2 \pm 0.15 -$ 

·∅I.4±0.15 -----

1.3±0.15

 $0.85 \pm 0.2$ 

 $-0.25\pm0.15$ 

1.7±0.15

THIS GROUND PAD-IS OPTIONAL

 $1.3 \pm 0.05$ 

1.3±0.05

SIGNAL PAD-

-GROUND

 $65 \pm 0.05$ 

— 0.5±0.05ТҮР.

RECOMMENDED PCB PATTERN

I.4±0.05 TYP

CENTER CONTACT-

 $- \emptyset 1.5^{+0.1}$ VISUAL--SIGNAL PAD 1.75±0.1 — ORIENTATION FEATURE 2 REF <del>()</del>--⊕  $\odot$  $\odot$ <del>-</del> (+)-5.52±0.1 | 12±0.3 | **|** 0 0 0 0 0 0 0 **→** 4±0.1 1.2±0.15 -SCALE 2.500

ECO

46540

50214

APPR

CPM

MJD

EMBOSSED CARRIER TAPE DIMENSIONS

UNREELING DIRECTION

## **CUSTOMER OUTLINE DRAWING**

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: MATERIAL DATE DRAWN ANGLES 0.5 - 6mm 6 - 30mm 30 - 120 mmAmphenol RF 10-May-07 H. PARIKH  $\pm\,$ 0.lmm  $\pm 0.2$ mm ± 0.3mm ASSEMBLY Danbury CT USA, Tainan, Taiwan, Shenzhen, China NOTICE - These drawings, specifications, or other data (I) are, and remain the property of Amphenol corp. (2) must be returned upon requiest; and (3) arre confidential and not to be disclosed to any person other than those to whom they ENGINEER DATE AMMC, JACK www.amphenolrf.com H. PARIKH 10-May-07 are given by Amphenol Corp. the funishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implicatioin or otherwise in any manner licensing, granting rights to permitting such holder or any other sperson to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data. REFERENCE APPROVED DATE DRAWING NO. A-2JA EAR # 966 AND M. HOYACK 5/16/07 SCALE: 30.0:1.0 SHEET I OF 2 ITEM NO. A-2JA CONFIGURATION LEVEL: CAD FILE DWG SIZE REV CODE ID В 74868 FINISH Root Folder/AMC/A-2JA PART NO. A-2JA