

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



### Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







PANEL CUT OUT

Ø16.00 0.00/+0.30 (.629 DIA .000/+.011)

### Mushroom head pushbutton switches

Distinctive features and specifications

A01M\_AX1607US



- Panel Sealed to IP65
- Single pole to four pole changeover
- Custom engraving
- Push on tab terminals
- ☐ 6A 250VAC

#### **ELECTRICAL SPECIFICATIONS**

- Current/Voltage Rating: 10mA 5VAC min, 6A 250VAC, 6Amp 12VDC
- Initial Contact Resistance : 10mΩ max at 1A 4VDC
- Insulation Resistance : 50MΩ min
- Dielectric Strength: 750V between open contacts, 5KV live to accessible
- Electrical Life: 50,000 cycles min
  Contact Gap: >1mm (0.039)
- Insulation : Class 2

#### MECHANICAL SPECIFICATIONS

- Mechanical Life (operator): Momentary, 1 million cycles, maintained 100,000 cycles
- Terminals: Solder/quick connect 2.8mm (0.110)

#### **GENERAL SPECIFICATIONS**

- Operating Temperature : -20°C to +55°C
- Solder Heat Resistance : 350°C for 5 seconds
- Sealing: Panel sealed to IP65, rear of panel IP40

#### AGENCY APPROVALS





#### **MATERIALS**

- Screens : PC
- Reflector assembly : PC
- Operator : PBT
- Nut : ABS
- Camtrack Momentary: PPE
  Camtrack maintained: PPSU
  Switch block 1 & 2 pole: PBT
  Switch block 3 & 4 pole: PEI
- Contacts: Gold plated silver



Dimensions : first dimensions are in mm while inches are shown in brackets. Refer to the following pages for further information.




Mounting accessories: standard hardware 1 nut and 1 sealing washer.

## Mushroom head pushbutton switches

Panel cut-out Ø16 (0.755)

#### **Pushbutton**




### Overview

	Operator		Switch	block	
Ø Actuator	Description	Part No	No of poles	Part No	
24mm	Black Momentary	A01MMA	Single pole	A0151B	
24mm	Red Momentary	A01MMB	Double pole	A0152B	
24mm	Yellow Momentary	A01MMD	Three pole	A0155B	
24mm	Green Momentary	A01MME	Four pole	A0153B	
24mm	Blue Momentary	A01MMF			
24mm	Black Maintained	A01MXA			
24mm	Red Maintained	A01MXB			
24mm	Yellow Maintained	A01MXD			
24mm	Green Maintained	A01MXE			
24mm	Blue Maintained	A01MXF			
40mm	Black Momentary	A01MMA SP3			
40mm	Red Momentary	A01MMB SP3			
40mm	Yellow Momentary	A01MMD SP3			
40mm	Green Momentary	A01MME SP3			
40mm	Blue Momentary	A01MMF SP3			
40mm	Black Maintained	A01MXA SP3			
40mm	Red Maintained	A01MXB SP3			
40mm	Yellow Maintained	A01MXD SP3			
40mm	Green Maintained	A01MXE SP3			
40mm	Blue Maintained	A01MXF SP3			


### Mushroom head pushbutton switches

Accessories


#### Flush mount bezels



#### **PCB Sockets**



### Terminal guards





## Mushroom head pushbutton switches

Accessories & tools

### Anti rotation ring

# Blanking plugs





#### **Tools**

