

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Innovative **Technology** for a **Connected** World

Tgrease[™] **1500 Series**Thermal Grease



Tgrease[™] 1500 SERIES SOLVES OVERHEATING AND RELIABILITY ISSUES

Tgrease[™] 1500 is environmentally safe silicone-based thermal grease designed to solve overheating and reliability issues.

Due to its proprietary silicone filler matrix, Tgrease 1500 thoroughly wets out contact surfaces to create a low thermal resistance of 0.021 °C-in2/W at 50 psi.

Tgrease 1500 can be used in pneumatic dispensing and screen printing systems.

Tgrease 1500 is available in 1kg (pint container), 2kg (quart container), and 7kg (gallon container) or custom packaged in syringes for automated applications.

FEATURES AND BENEFITS

- Environmentally safe
- Thoroughly wets out contact surfaces to create low thermal resistance
- Available in 1/2kg, 1kg, 3kg, 7kg, 20kg bulk container, and 10cc, 30cc syringe

APPLICATIONS

- Microprocessors
- Chipsets
- Graphic processing chips
- Custom ASICS
- IGBT
- TO220, TO240, and other standard packages
- Power supplies

global solutions: local support ™


USA: +1.800.843.4556 Europe: +49.8031.2460.0 Asia: +86.755.2714.1166


CLV-customerservice@lairdtech.com www.lairdtech.com/thermal



Tgrease[™] **1500 Series**Thermal Grease

| TYPICAL PROPERTIES | TGREASE™ 1500 | TEST METHOD |
|---|-------------------------------------|--|
| Color | White | Visual |
| Density | 2.6 g/cc | |
| Viscosity @ 22°C | 1.5 x 10 ⁶ | Brookfield DV-II+ Spindle –T-F; Speed 2rpm |
| Maximum Operating Temperature | 125°C | |
| Outgassing (TML) | 0.79% | ASTM E595 |
| Outgassing (CVCM) | 0.12% | ASTM E595 |
| UL Flammability Rating | Pending | |
| Thermal Conductivity | 1.2 W/mK | Hot Disk Thermal Constants Analyzer |
| Thermal Resistance @ 50 psi @ 344.7 KPa | 0.021 °C-in²/W 0.135 °C-cm²/W | ASTM D5470 (modified) ASTM D5470 (modified) |
| Volume Resistivity | 7 x 10 ¹¹ @ 100 volts DC | ASTM D257 |
| Dielectric Constant @ 1KHz/1MHz | 5.9 / 5.8 | ASTM D150 |
| | | |





Data for design engineer guidance only. Observed performance varies in application. Engineers are reminded to test the material in application.