



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Tflex™ XS400 Series Gap Filler Material

Compliant 2.0 W/mK Thermally Conductive Gap Filler

[Stock Locator](#)

Tflex™ XS400 is a compliant elastomer gap filler designed to provide moderate thermal performance. This soft interface pad conforms well with minimal pressure, resulting in little or no stress on mating parts. Tflex™ XS400 is naturally tacky, no adhesive coating is required. Due to its TG liner on the other side, Tflex™ XS400 is electrically insulating, stable from -40°C to 160°C and is certified to UL 94V0 flammability rating.

Results 1 - 19 of 19

Item #	Color	Thickness	Hardness	Outgassing TML	Outgassing CVCM
Tflex XS420	Dark Grey / Red Liner	0.020 inches 0.508 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS430	Dark Grey / Red Liner	0.030 inches 0.762 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS440	Dark Grey / Red Liner	0.040 inches 1.02 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS450	Dark Grey / Red Liner	0.050 inches 1.27 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS460	Dark Grey / Red Liner	0.060 inches 1.52 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS470	Dark Grey / Red Liner	0.070 inches 1.78 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS480	Dark Grey / Red Liner	0.080 inches 2.03 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS490	Dark Grey / Red Liner	0.090 inches 2.29 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4100	Dark Grey / Red Liner	0.100 inches 2.54 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4110	Dark Grey / Red Liner	0.110 inches 2.79 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4120	Dark Grey / Red Liner	0.120 inches 3.05 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4130	Dark Grey / Red Liner	0.130 inches 3.30 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4140	Dark Grey / Red Liner	0.140 inches 3.56 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4150	Dark Grey / Red Liner	0.150 inches 3.81 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4160	Dark Grey / Red Liner	0.160 inches 4.06 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4170	Dark Grey / Red Liner	0.170 inches 4.32 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4180	Dark Grey / Red Liner	0.180 inches 4.57 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4190	Dark Grey / Red Liner	0.190 inches 4.83 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4200	Dark Grey / Red Liner	0.200 inches 5.08 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %

Results 1 - 19 of 19